N. M. OIL CONS. COMMISSION

Form Approved. Budget Bureau No. 42-R1424

UNLIED STATES. BOX 1930 DEPARTMENT OF THE INTERIOR MEXICO 89	240 LEASE
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas X other	Federal Com. 7 9. WELL NO.
2. NAME OF OPERATOR	1
Inexco Oil Co.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR 211 Highland Cross, Suite 201 Houston Tx. 7707	311. SEC., T., R., M., OR BLK. AND SURVEY OR
4. Education of Weel (Ref out Location decane), see space 17	AREA Sec.7,T19S,R33E
below.) AT SURFACE: 1980' FNL & 660'FEL.	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Lea NM
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	<u> </u>
TEST WATER SHUT-OFF	
FRACTURE TREAT SHOOT OR ACIDIZE SHOTT OR ACIDIZE	
REPAIR WELL PULL OR ALTER CASING T	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
MULTIPLE COMPLETE	्र ज ्र
CHANGE ZONES	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner	e all pertinent details, and give pertinent dates, irectionally drilled, give subsurface locations and it to this work.)*
Set CIBP @ 13,100'.Dumped 35'cement on top.	
Cut 5 1/2 "casing @ 5574'. POOH & LD 135joints RIH w/2 7/8" tubing to 7690'. Set 170' cement Pulled EOT to 5624'. Set 100' cement plug from Pulled EOT to 4200'. RIH to 5447', tagged plug. Pulled EOT to 5150'. Set 100' cement plug from Pulled EOT to 2500'. Set 100' cement plug from	plug from 7690'-7520' w/25 sx. a 5624' to 5524'w/50 sx. Held OK. a 5150' to 5050'w/60 sx.
Pulled EOT to 560'. Set 100' plug from 560'-46 Cut 8 5/8" casing off 4' below ground level. Set plug at surface w/ 15 sx. Welded on 1/2" steel plate, set dry hole marker	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED 7 Grant Grant Prod. Clerk (This space for Federal or State off	DATE9-6-83
Orig. Sgd PETER W. EFFESTER TITLE CONDITIONS OF APPROVAL; IF ANY:	ice use)