

9. WELLSITE LAYOUT:

- A. Exhibit "D" shows the relative location and dimensions of the well pad, mud pits, reserve pit, trash pit, and location of major rig components.
- B. Only minor levelling of the wellsite will be required. No significant cuts and fills will be necessary.
- C. The reserve pit will be plastic-lined.
- D. The pad and pit area has been staked and flagged.

10. PLANS FOR RESTORATION OF THE SURFACE:

- A. After completion of drilling and/or completion operations, all equipment and other material not needed for operations will be removed. Pits will be filled and location cleaned of all trash and junk to leave the wellsite in an aesthetically pleasing condition as possible.
- B. Any unguarded pits containing fluids will be fenced until they are filled.
- C. After abandonment of the well, any special rehabilitation and/or revegetation requirements of the surface management agency will be complied with and accomplished as expeditiously as possible. All pits will be filled and levelled within 90 days after abandonment.

11. OTHER INFORMATION:

- A. Topography: Land surface is undulating to gently rolling and dunny. From an elevation of 3658 feet at the wellsite, the land surface slopes gently toward the south at about 30 feet per mile.
- B. Soil: Soil is a deep fine sand and underlain by caliche.

CONFIDENTIAL
MAY 1977
CONFIDENTIAL