

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR
Inexco Oil Company

3. ADDRESS OF OPERATOR
211 Highland Cross Suite 201 Houston, Tx 77073

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980'N 660'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:
TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other)

SUBSEQUENT REPORT OF

RECEIVED

JAN 25 1983

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set CIBP @ 10,750 with 35' Cement on top
Cut Casing Approximately 10,000'. 100' cnt plug, 50' in & out of stub.
Set Cement Plug @ 150' A Cut Off (If Casing not free at 10,000 Cut at 7500
* set Plug at Cut off - 7500' 75' in and 75' out.)
If Pipe Cut below 7600' Set 150' Plug @ 7650' - 7550'. Tag this plug.
Set Cement 5180 - 5030, 150' Plug . Tag this plug.
Set Cement 1500 to 1400, 100' Plug
Set Cement 560 - 460, 100' Plug
50' Surface and Dry Hole Marker

OK

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

APPROVED

(This space for Federal or State office use)

APPROVED BY

W. CHESTER

DATE

CONDITIONS OF APPROVAL, IF ANY:

JAN 25 1983

FOR

JAMES A. GILLHAM *See Instructions on Reverse Side
DISTRICT SUPERVISOR