

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPL
(Other instructions
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-0554244

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "L"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT
Guerecho Plains - Upper
Bone Springs

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

23-18S-32E

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR

Mewbourne Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 7698, Tyler, Texas 75711

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

660' FSL & 1980' FEL

14. PERMIT NO.

API #30-025-29674

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3766.5' GR

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) Setting Surface Casing

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/23/86 - Spudded at 2:00 P.M. 4/22/86. Ran guide shoe, 42' shoe joint, insert float, 3 centralizers, 11 joints 13-3/8" 61# (459'). Total 459' set at 459'. Western cemented with 200 sacks of Class "C" with 6% gel + 2% CaCl 1/4# flocele and 200 sacks of Class "C" with 2% CaCl. PD to 459' at 3:15 A.M. Circulated 50 sacks.

ACCEPTED FOR RECORD

Gué
MAY 5 1986

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Raymond Simpson

TITLE

Engr. Oprns. Secretary

DATE

4/30/86

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side