

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION  
P O BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S		
LAND OFFICE		
OPERATOR		

API No. 30-025-30481

5a Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5 State Oil & Gas Lease No B-2148	
7 Unit Agreement Name	
8 Farm or Lease Name Leamex	
9 Well No 56	
10 Field and Pool, or Wildcat Maljamar Gb/SA	
12 County Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO CLEAN OR PLUG BACK TO A DIFFERENT RESERVOIR  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

11  
OIL WELL  GAS WELL  OTHER

12 Name of Operator  
Phillips Petroleum Company

13 Address of Operator  
4001 Penbrook Street, Odessa, Texas 79762

14 Location of Well  
UNIT LETTER P 660 FEET FROM THE east LINE AND 660 FEET FROM  
THE south LINE, SECTION 23 TOWNSHIP 17-S RANGE 33-E NMPM

15. Elevation (Show whether DF, RT, GR, etc.)  
4130.7' GR unprepared

16 Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK
- TEMPORARILY ABANDON
- PULL OR ALTER CASING
- OTHER \_\_\_\_\_
- PLUG AND ABANDON
- CHANGE PLANS

SUBSEQUENT REPORT OF:

- REMEDIAL WORK
- COMMENCE DRILLING OPNS.
- CASING TEST AND CEMENT JOB
- OTHER \_\_\_\_\_
- ALTERING CASING
- PLUG AND ABANDONMENT

17 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103

10-17-88: Spud 12-1/4" hole at 6:54 a.m. MST.

10-18-88: Td'd 12-1/4" hole at 10:15 a.m. MST. Set 8-5/8" 24# K-55 ST&C casing at 1525' from 1000 sxs Class "C" with 2% CaCl. Circ 180 sx cmt. Approximate temperature of cement slurry when mixed 80°, estimated formation temperature 65°, cement strength at time of test exceeded 1000 psi. Total WOC time 9½ hrs.

10-19 thru

10-21-88: Dr1g 7-7/8" hole.

10-22-88: Td'd 7-7/8' hole at 11:15 a.m. Ran CNL-LDT-GR-Cal from TD at 4800' to 2500' and CNL-GR-Cal from 2500' to surface.

SEE REVERSE SIDE

18 I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton W. J. Mueller TITLE Engineering Supervisor, Reserv. DATE 10-26-88

APPROVED BY JERRY SEXTON DISTRICT I SUPERVISOR TITLE \_\_\_\_\_ DATE 10 26 1988

10-23-88: Set 5-1/2" 15.5# K-55 ST&C casing at 4800' with 1000 sx Howco Lite,  
5% salt and 300 sx Class "C" Neat. Circ 220 sx cmt. ND BOP, set  
csg slips and cut csg. Released rig.  
Waiting on completion unit.

**RECEIVED**  
**NOV 2 1988**  
**OCD**  
**HOBBS OFFICE**