

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT NEW MEXICO 83240

5. LEASE DESIGNATION AND SERIAL NO.

NM-0997 LC-064944
IF INDIAN, ALLOTTEE OR TRIBE NAME

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1A. TYPE OF WORK

DRILL ☒

DEEPEN ☐

PLUG BACK ☐

b. TYPE OF WELL

OIL WELL ☒

GAS WELL ☐

OTHER

SINGLE ZONE ☒

MULTIPLE ZONE ☐

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

21 Desta Drive, Midland, Texas 79705

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)*
At surface

1980' FEL & 660' FNL

At proposed prod. zone

810

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*

14 miles southeast of Maljamar, NM

10. DISTANCE FROM PROPOSED LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT.
(Also to nearest drlg. unit line, if any)

3,300'

16. NO. OF ACRES IN LEASE

1,600

17. NO. OF ACRES ASSIGNED TO THIS WELL

80

18. DISTANCE FROM PROPOSED LOCATION* TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT.

3,000'

19. PROPOSED DEPTH

11,450'

20. ROTARY OR CABLE TOOLS

Rotary

21. ELEVATIONS (Show whether DF, RT, GR, etc.)

3,849' G.L.

22. APPROX. DATE WORK WILL START*

04/15/89

23. PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
17-1/2"	13-3/8"	48#	350'	350 sx Cl. "C" CIRCULATE
12-1/4"	8-5/8"	24# & 28#	2900'	1400 sx Lite "C" CIRCULATE
7-7/8"	5-1/2"	15.5# & 17#	11450'	2100 sx. TOC @ 2900'

Drill 17-1/2" hole to 350'. Set 13-3/8" csg @ 350', Cmt w/350 sx Cl "C", Circ. Drill 12-1/4" hole to 2900'. Run fluid caliper. Set 8-5/8" csg @ 2900'. Lead w/1200 sx Lite "C", tail in w/200 sx Cl "C", Circ. Drl to TD to test Middle & Lower Wolfcamp. If commercial, run 5-1/2" csg to 11,450'. Cmt w/sufficient volume to bring above all prospective zones. Est TOC @ 2900'. Perf & stimulate Wolfcamp for production.

MUD PROGRAM: 0-350' spud mud; 350-2900' brine; 2900-10200' cut brine & sweeps (chloride 30,000+). 10,200-TD cut brine & Drispac. MW 9.0-9.2 (Solids must be less than 5% w/VIS 32-36).

BOP PROGRAM: 13-5/8"-2M annular BOP to be installed on 13-3/8" csg. 11"-3M stack to be installed on 8-5/8" & left on for remainder of drlg. Stack to consist of annular BOP, blind ram BOP & one pipe ram BOP. Test BOP's after setting 8-5/8" csg with an independent tester.

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24.

SIGNED

Robert L. Bradshaw

TITLE Sr. Staff Env./Reg. Spec

DATE

02/09/89

(This space for Federal or State office use)

PERMIT NO.

APPROVAL DATE

APPROVED BY

Sup. Staff Env./Reg. Spec

TITLE

Sup. Staff Env./Reg. Spec

DATE

3-9-89

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions On Reverse Side

RECEIVED

MAR 10 1959

OCD
HOBBS OFFICE