

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PROGRATION OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in **TRIPPLICATE** to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

November 23, 1964
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Cactus Drilling Company Hooper "A" Well No. 1 in Lease (Unit)
(Company or Operator)
NW 1/4 SW 1/4 of Sec. 6, T. 19 S, R. 35 E, NMPM., Scharb Bone Springs Pool
(40-acre Subdivision) Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Subject well having become a non-commercial producer, we propose to plug and abandon same using following plugging program: (verbal permission secured from Mr. Joe D. Ramsey to proceed)

- 15 sx cement plug set at 9475-97;
- 25 sx cement plug set at shoot-off point (approx 7000');
- 25 sx cement plug set at 6050;
- 25 sx cement plug set 3974 (in and out of 8-5/8" intermediate strg);
- 25 sx cement plug set 1900;
- 25 sx cement plug set 400 (in and out of 13-3/8" Surf. csg.);
- 10 sx cement plug set at surface.

Lease will be cleared of all equipment, surface area returned to original contour, and appropriate marker placed to identify the location.

Approved....., 19.....
Except as follows:

CACTUS DRILLING COMPANY
Company or Operator

By.....

Position Production Supt

Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

Name Mr. Geo. W. Baker

By.....

Address Box 1826, Hobbs, New Mexico

Title.....