get Bureau No. 42-R358.4.

		1 001	
Form 9-331a (Feb. 1951)	HUBBS (SUBMIT IN TRIPLICATE)	Land Office	Naw Naxico 073240
	ACCOVED TRIPLICATES JUL 28 DEPARTMENT OF THE INTERIOR CEOLOGICAL SURVEY	Unit	<u>C</u>
	GEOLOGICAL SURVEY		
	J. L. GORDON ANTING DISTRICT ENGINEER		

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO TEST WATER SHUT-OFF NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL		SUBSEQUENT REPORT OF WATER SHUT-OFF. SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING. SUBSEQUENT REPORT OF ALTERING CASING. SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR. SUBSEQUENT REPORT OF ABANDONMENT. SUPPLEMENTARY WELL HISTORY.	
--	--	--	--

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

	harch 25, 19				
Signal Ross Well No. #6 is located		1980 ft. fr	om $\{E\}$ line of se	с. 30	
SU/A SE/A Sec. 30 ()4 Sec. and Sec. No.) Vildcat (Field)	(Range) 2 unty or Subdivision)	(Meridian)	New Piex LCO (State or Territory)	-	

The elevation of the derrick floor above sea level is 3583 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On March 11, 1964, this well was plugged and abandoned as follows:

Cut and pulled 5% casing from 2810'. Placed 70 saks cement from 2810 to 2600'. Placed 35 sacks cement from 1375 to 1275'. rulled 10" and 8" cave strings. Placed 60 sacks coment from 675 to 575. Placed cement plug in top 12' of 13-3/8" casing. Set 4" pipe parker at surface.

I understar	william A. & Marard & Hudson,	by the Geological Survey before operations may be commenced. it Agent
	302 Carper Building	^
	Artesia, New Harico	By Rayh I may
		Title Consulting Engineer.
		GPO 914974