

COUNTY	LEA	FIELD	Midway	STATE	NM
OPR	SINCLAIR OIL & GAS COMPANY				MAP
1 Selby, C. M.					
Sec. 18, T-17-S, R-37-E					
1980' FNL, 1980' FEL of Sec.				CO-ORD	
Spd 6-3-66				MN	21784
Cmp 7-14-66		CLASS		E	
CSG & SX - TUBING		FORMATION	DATUM	FORMATION	DATUM
13 3/8" 352' 360					
8 5/8" 4800' 2700					
4 1/2" 9020' 395					
LOGS EL GR RA IND HC A					
		TD 9020', PBD 9001'			
IP Bone Spring Perfs 8965-8990' Flwd 288 BOPD. Pot. Based on 16 hr test of 192 BO thru 18/64" chk., TP 100#, Gravity 32.2, GOR 870.					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Leatherwood Drlg. Co. PROP DEPTH 9100' TYPE
DATE

F.R. 5-26-66
PD 9100' - Abo
Contractor - Leatherwood Drlg. Co.
6-7-66 Drlg. 2027' anhy.
6-9-66 Drlg. 2730' anhy & salt.
6-21-66 TD 4286', stuck Drill Pipe.
6-28-66 TD 4800' lm., WOC.
7-5-66 Drlg. 6490' lm.
7-11-66 Drlg. 7112' lm & sh.
7-18-66 Drlg. 8949' lm & dolo.
7-25-66 TD 9020', PBD 9001', COMPLETE.
DST 8898-8995', open 2 hrs,
GTS 7 mins @ 210 MCFGPD decreasing to
175 MCFGPD @ end of test,
Rec 5000' free oil (Gravity 30.)
Rec 180' O&GCM below sub,
1 hr ISIP 2514#, FP 231-886#,
2 hr FSIP 2430#.

7-25-66

Cont.

Perf @ 8965', 8975', 8981', 8984', 8990'

W/2 SPI

Acid (8965-90') 500 gals.

Max press. 5500#; Inj @ 3/4 BPM

Acid (8965-90') 2000 gals.

Max press. 5700#; Inj @ 2.5 BPM

LOG TOPS: Anhydrite 1990', Yates 3200',

San Andres 4994', Glorieta 6605', Tubb

7770', Abo 8380', Bone Spring 8898'.