

Pipeline Deep Unit Federal

Well No. 5

OPERATOR: Union Oil Company of California

REPORT NATURE: Complete as Salt Water Disposal

- jates
- 6-11-81 Tag cement @ 5,175'. Rig up and perf. 9-5/8" OD casing 3,895' - 4,233'.
 - 6-12-81 Set pkr @ 3,850', acidize perfs 3,895' - 4,233' w/10,000 gals. 20% HCl acid.
 - 7- 7-81 Perf 9-5/8" OD casing 4,445' - 4,455' w/1 SPF and 3,712-14', 3,726-28', 3,747-49' 3,765-67' and 3,799' - 3,801' w/2 SPF.
 - 7- 8-81 Ran 9-5/8" Guiberson unipacker on 2-3/8" OD tubing @ 4,263'. Acidized perfs 4,445' - 4,455' w/3000 gals. 20% HCl acid.
 - 7-10-81 W/bridge plug @ 3,872' and RTTS pkr at 3,841' acidized perfs 3,712' - 3,801' w/4500 gals 20% HCl acid.
 - 7-11-81 Ran Guiberson unipacker to 3,675' on 118 jts. 2-3/8" OD tubing (PCID). Displace casing & tubing annulus w/pkr fluid.
 - 7-25-81 Ran step rate test and place well on SWD service.