

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

API NO. 30-025-26778

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
B-1497	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name
2. Name of Operator	East Vacuum Gb/SA Unit
3. Address of Operator	8. From or Lease Name
Room 401, 4001 Penbrook St., Odessa, Texas 79762	East Vacuum Gb/SA Unit, Tract 2721
4. Location of Well	9. Well No.
UNIT LETTER N, 2600 FEET FROM THE West LINE AND 1300 FEET FROM THE South LINE, SECTION 27 TOWNSHIP 17-S RANGE 35-E N.M.P.M.	002
15. Elevation (Show whether DF, RT, GR, etc.)	10. Field and Pool, or Wildcat
3931' GR.	Vacuum Gb/SA
12. County	
	Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	
		OTHER Total depth ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-5-80 MI Marc Drlg. Repairing rig.

6-9-80 Spud in w/12-1/4" hole. Ran 9 jts 9-5/8", 36#, K-55 csg set at 360'. Cmt w/400 sxs Cl "H" w/2% CaCl, 1/4#/sx Flocele. Circ 34 sxs to surf. Temp cmt slurry when mixed 60°, temp in zone 75°, est strength at time of testing 1500#. Cmt in place 11-1/2 hrs prior to test. Tested BOP's and csg 1000 psi, OK.

6-24-80 Reached 4800' TD. Running logs.

6-25-80 Ran 5-1/2", 14#, K-55 csg set at 4789'. Cmt w/400 sxs Cl "H" w/8#/sx salt and 1200 sxs TLW w/12#/sx salt, 1/4#/sx Flocele, 10% DD and 3#/sx Gilsonite. Circ 100 sxs.

6-26-80 Released rig--prep to complete.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller TITLE Sr. Engineering Specialist DATE June 26, 1980

APPROVED BY John Runyan TITLE Geologist DATE JUN 30 1980

CONDITIONS OF APPROVAL, IF ANY: