

CHECK LIST AND DRAWINGS (ATTACHED)  
 MINIMUM BLOWOUT PREVENTER EQUIPMENT REQUIREMENTS  
 (ATTACHMENT NO. 2 TO BID SHEET AND WELL SPECIFICATIONS)  
5000 PSI WORKING PRESSURE  
 TO BE INSTALLED AFTER SETTING 8-5/8 INCH CASING

ATTACHMENT NO. 2  
 (See Section 4)  
 Page 1 of 1

Contractor or Pzl. to furnish items checked (X). See attached drawing.

No.	Item	Min. Size *	Type	Press. Rating	Furnished By	
					Contr.	Pzl.
1.	Flow Line	8"	Weld	125	X	
2.	Fill Up Line	2"	Thd or Weld	125	Y	
3.	Bell Nipple	8"	Weld	125	Y	
4.	Rotating Head					
5.	Hydraulically Operated Gate Valve					
6.	Blooe Line					
7.	Bog Preventer	8"	Flange	5000	Y	
8.	Hydraulically Operated Ram Preventer or Rotating Head					
9.	Drilling Spool with <u>2</u> in. and <u>2</u> in. Side Outlets	8"	Flange	5000	X	
10.	Preventer Side Outlets, <u>2</u> in. and <u>2</u> in. Use as alternate to No. 9 above.	8"	Flange	5000	X	
11.	Gate Valve	2"	Flange	5000	X	
12.	Hydraulically Operated Gate Valve					
13.	Line to Choke Manifold	2"	Flange	5000	Y	
14.	Gate Valve	2"	Flange	5000	Y	
15.	Hydraulically Operated Gate Valve					
16.	Check Valve					
17.	Drilling Spool with _____ in. and _____ in. side outlets					
18.	Preventer Side Outlets _____ in. and _____ in. Use as alternate to No. 17 above.					
19.	Gate Valve	2"	Flange	5000		X
20.	Hydraulically Operated Gate Valve					
21.	Relief Line					
22.	Wear Flange or Bushing	N/A				
23.	Kill Line to accessible location approx. _____ ft. from rig.					
24.	Gate Valve					
25.	Kill Line to rig pump manifold	2"	Flange	5000	X	
26.	_____ Way Cross, _____ in. x _____ in. x _____ in. x _____ in.					
27.	Tee, _____ in. x _____ in. x _____ in.					
28.	Half Union					
29.	Casing Spool					
30.	Gate Valve					
31.	Casing Spool					
32.	Gate Valve					
33.	Pressure Gauge					
34.	Casing Head	8"	Flange	5000		X
35.	Gate Valve					
36.	Gate Valve					

\* Line sizes to be inside diameter.  
 Valves, spools and preventer sizes to be bore dimension.

RECEIVED

JUN - 3 1985

G.C.D.  
HOBBS OFFICE