


Land Office New Mexico
Lease No. NM 0149957
Unit Little Eddy

Form 9-381a
(Feb. 1961)

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
1962 JUN 27 AM 9 50



SUNDRY NOTICES AND REPORTS ON WELLS

| | | | |
|--|---|--|--|
| NOTICE OF INTENTION TO DRILL | | SUBSEQUENT REPORT OF WATER SHUT-OFF | |
| NOTICE OF INTENTION TO CHANGE PLANS | | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | X | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | | SUBSEQUENT REPORT OF ABANDONMENT | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. Brooks-7 3 is located 660 ft. from N line and 1980 ft. from E top line of sec. 7
Date May 10, 1962

SEK 7 (1/4 Sec. and Sec. No.) 20 S (Twp.) 33 E (Range) NMPM (Meridian)
Salt Lake (Field) 1 CA (County or Subdivision) New Mexico (State or Territory)

RECEIVED
MAY 14 1962
U. S. GEOLOGICAL SURVEY
ARIZONA, NEW MEXICO

The elevation of the derrick floor above sea level is 3503 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This well was originally completed by The Continental Oil Co. as their Brooks-7 No. 3 on 10-14-42 for 288 BOPD for the Yates-Seven Rivers Reef pay producing from the open hole interval 2887-3025 with the following casing program 10-3/4" @ 606 mudded, 8-5/8" @ 1162' cemented with 350 sacks. 5 1/2" at 2887' cemented with 100 sacks. In November 1948 the well was plugged and abandoned in the following manner: Cement plug from 3025 to 2900 3 1/2" casing shot off @ 1105. A cement plug from 1050-1150. 8-5/8" shot off @ 250' a cement plug from 300 to 200' and 50' to surface. We now request permission to workover and repair this well in the following manner: Attempt to clean out to TD. Run electric & gamma ray logs, check for collapsed casing with tools and logs run 4 1/2" J-55 9 1/2" casing from TD to surface and cement with sufficient volume to circulate. In the event the well is non-commercial place solid cement plug thru salt section. Also across water zones at 1162' 458' and 409' place 50' cement plug to top. All state and federal regulations will be complied with. (over)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Randall F. Montgomery
Address P. O. Box 2414
Hobbs, New Mexico

By R. F. Montgomery
Title Lessee

Estimated tops

| | |
|---------------|-----------|
| Top Anhydrite | 1120 |
| Top Salt | 1280 |
| Base Salt | 2620 |
| Show Oil | 2975-3025 |
| TD | 3025 |

Cumulative production to date 35,662 bbls. oil and 103,846 bbls. water.