

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other Water Injection Well

2. NAME OF OPERATOR
Anadarko Production Company

3. ADDRESS OF OPERATOR
P.O. Box 806 Eunice, New Mexico 88231

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL & 660' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: XX SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF
FRACTURE TREAT
~~SEAL OFF~~ ACIDIZE
REPAIR WELL
PULL OR ALTER CASING
MULTIPLE COMPLETE
CHANGE ZONES
ABANDON*
(other) Plus clean out.

MAY 13 1983

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

ROSWELL, NEW MEXICO

5. LEASE
NM 01059
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Teas Yates Uint
8. FARM OR LEASE NAME
Tract 2
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Teas
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 15, Twp 20S, Rg 33E
12. COUNTY OR PARISH | 13. STATE
Lea | NM
14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3375' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. RUPU. TOH w/2-3/8" Salta lined tbg & inj pkr.
2. TIH w/4-1/8" bit on 2-7/8" workstring. Tagged up @ 3848'. TOH w/bit.
3. TIH w/5 1/2" treating pkr. RU dresser Titan. Acidized w/3000 gals 20% NE-FE acid in two stages using 500# rock salt as blocking agent. Flushed w/75 bbls 2% KCL. ISIP 2300# Psi. TOH w/treating pkr.
4. TIH w/104 jts of 2-3/8" (3218') of Salta lined tbg & Guiberson Uni-1 PKR. Circ pkr fluid. Set Pkr @3220'.
5. Resumed water injection 4-20-83.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Original Edward R. Zerkett TITLE Field Foreman DATE May 9, 1983

ACCEPTED FOR RECORD (space for Federal or State office use)

APPROVED BY (ORIG. SGD.) DAVID R. GLASS DATE _____

CONDITIONS OF APPROVAL SEP 06 1983

ROSWELL, NEW MEXICO