



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Page 2

Budget Bureau No. 43-1336-1
Approval expires 12-31-60.

Local Office

Lease No.

HOBBS OFFICE OCC

Unit

NOV 27 PM 3:43

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Federal #C¹²

Well No. 1 is located ft. from $\begin{Bmatrix} N \\ S \end{Bmatrix}$ line and ft. from $\begin{Bmatrix} E \\ W \end{Bmatrix}$ line of sec. 19

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

jet shots, treated perfs 12,572'-12,586' w/ 500 gallon mud acid. Placed cement plug in 7" casing 12,600' to 12,500' with 12 sacks. Shot 7" casing off at 4029', pulled 7" casing, placed cement plug in 7" casing 6530'-5470' w/ 12 sacks, 4220'-4100' w/ 24 sacks, 4040'-3940' w/ 40 sacks, 20' to surface w/ 8 sacks. Welded 1/2" steel plate on top casing with 4" marker extended 4' above surface.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company

Address

By

Title