



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. N.M. 0897
Unit Lease

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	X	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Fletcher "A"
Well No. 1 is located 990 ft. from N line and 990 ft. from W line of sec. 35
October 23, 1956

NW/4 Section 35 20 S 34 E NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Lynch Lea New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3730 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled to total depth 3725 Sandy Lime. Plugged back to 3682 with Caliche Rock and 2 sacks Calseal. Ran 5 1/2-inch casing and set on bottom. Pulled 8 5/8 inch, 10 3/4 inch and 13 3/8 inch casing. Picked up 5 1/2 inch casing and cemented at 3680 with 1550 sacks. Cement circulated. Plug down at 4:00 P.M. 10-22-56. Top plug 3660. Will WOC 30 hours and bail hole dry.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Drilling & Exploration Company, Inc.

Address Box 2075

Hobbs, New Mexico

By D.C. Miller
Title Division Prod. Superintendent