

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PRORATON OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the person on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	<b>X</b>
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(Place)

January 24, 1963  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

**Gulf Oil Corporation** **Lea State "A"** Well No. **1** in **A** (Unit)  
 (Company or Operator) Lease

**NE**  $\frac{1}{4}$  **NE**  $\frac{1}{4}$  of Sec. **32**, T. **19-S**, R. **35-E**, NMPM., **Pearl Queen** Pool  
 (40-acre Subdivision)

**Lea** County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 4970'.

It is proposed to drill deeper and recomplate as follows:

1. Move in cable tool unit and drill 35' from old TD 4970' to 5005'.
2. Run GR-N log. Dump, with bailer, sufficient 15% NE acid to cover open hole.
3. Establish injection rate, drop total of 70, 7/8" RCNB sealers to block old perforations. (4926' to 4932')
4. Free down casing with 2, 5000 gallon stages of gelled lease oil with 1/40# Adomite M-11 and a maximum of 1/4# SPG.
5. Run 2-3/8" tubing with Baker FB retrievable packer, set packer at approximately 4950'.
6. Test from below packer as necessary to evaluate zone productivity.
7. Remove packer and return well to production.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION  
By.....  
Title.....

**Gulf Oil Corporation**  
Company or Operator

By *[Signature]*

Position **Area Production Manager**  
Send Communications regarding well to:

Name **Gulf Oil Corporation**

Address **Box 2167, Hobbs, New Mexico**