

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Artec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WI	JPI NO.
	30-025-03276
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	
6. State Oil & Gas Lease No. E-5886	
7. Lease Name or Unit Agreement Name West Pearl Queen Unit	
8. Well No. 149	
9. Pool name or Wildcat Pearl Queen	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER TA-Oil Well
2. Name of Operator Pyramid Energy, Inc.
3. Address of Operator 10101 Reunion Place, Ste. 210 San Antonio, TX 78216
4. Well Location Unit Letter <u>G</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>1980</u> Feet From The <u>East</u> Line Section <u>32</u> Township <u>19S</u> Range <u>35E</u> NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3720' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

05/27/94 Tag CIBP at 4740' and circulate hole with mud. Spotted 25 sack cement plug on top of CIBP. Spotted 25 sack cement plug at 1900'. Pumped 198 sacks cement down 4 1/2" casing through casing leak at 186'. Circulated cement through leak at 186' back to surface between 4 1/2" and 8 5/8" casing. Left cement plug inside 4 1/2" casing from surface down to 186'. Cut off casing 3' below ground level and welded on cap and marker. Well plugged and abandoned 05/27/94.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Scott Graef TITLE Operations Manager DATE 06/01/94

TYPE OR PRINT NAME Scott Graef TELEPHONE NO. (210) 308-8000

(This space for State Use)

APPROVED BY Carmy W. Hill TITLE OIL & GAS INSPECTOR DATE _____

CONDITIONS OF APPROVAL, IF ANY:

JCS

CP

