

TRIPlicate

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

FEB 20 1945

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

Hobbs, New Mexico

Place

Feb. 16, 1945

Date

OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Stanolind Oil & Gas Co.

State "N"

Well No. 1

in the

Company or Operator

Lease

C NW/4 of NW/4

of Sec. 32

T. 19-S

R. 35-E

, N. M. P. M.,

Wildest

Field,

Lee

County.

The dates of this work were as follows:

From Nov. 15, 1944 to Nov. 30th.

Notice of intention to do the work was (was not) submitted on Form C-102 on November 14 19 44

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

This well was drilled to a total depth of 3985 on November 14, 1944, and due to low structural condition, it was decided to plug and abandon at this depth--details of work performed were as follows: Spotted a 20-sack cement plug from 3100' to 3160' after filling hole with heavy mud fluid from total depth of 5985 9-5/8" casing was shot-off at intervals from 2780' to 2340' and 2275' was recovered. Set Cement plug from 1808 to 1840, and filled hole with heavy mud to 15' from surface. A 15-sack cement plug was placed in top of hole and set 4" pipe marker which extends 5' above surface of ground. All surplus material was moved from location, and terrain restored to its original contours. Pits and cellar was filled and smoothed.

Witnessed by C. V. Campbell Name Stanolind Oil & Gas Company Production Foreman Title

Subscribed and sworn before me this 16

I hereby swear or affirm that the information given above is true and correct.

day of February, 19 45

Name Joseph L. Hennrichson

Position Field Supt -

R. M. Russell Jr. Notary Public

Representing Stanolind Oil & Gas Co Company or Operator

My commission expires 5-5-47

Address Box 7 Hobbs - N Mex

Remarks:

Roy Garbrough. Name Title