

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

RECEIVED
NOV 16 1944

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL			

Hobbs, New Mexico

November 14, 1944

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the Stanolind Oil & Gas Company State "M" Well No. 1 in C NW/4 of NW/4 Company or Operator Lease of Sec. 32, T. 19-S, R. 35-E, N. M. P. M., Wildcat Field, Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

The subject well was spudded on October 14, 1944, and drilled to a total depth of 3895' with rotary tools. Top of rustler anhydrite was encountered at 1800'; base of salt 3300'; and top of Yates Sand at 5520'. Due to the apparent low structural position of this well, we propose to abandon same at its present depth in the following manner: Place a 20-sack cement plug at 3300' in the 9-5/8" casing which was set w/ 250 sacks of cement at 3334'; then part the 9-5/8" and recover as much as possible (est. 2600'). Place a 30-sack cement plug in the rustler anhydrite above the salt at 1850; leave all the 15" surface pipe which was cemented from 330 to surface, and fill the top joint w/ cement, into which will be placed a 4" pipe marker, extending 5 ft. above the ground level. The hole will be kept full of heavy mud laden fluid between all cement plugs. The cellar and pits will be filled and the surface terrain restored to natural surroundings.

Approved NOV 16 1944, 19____
except as follows:

Stanolind Oil & Gas Company
Company or Operator

By Ralph L. Hendrickson

Position Field Superintendent

Send communications regarding well to

Name Mr. Ralph L. Hendrickson

Address Box "F"

Hobbs, New Mexico

OIL CONSERVATION COMMISSION,
By Roy Yarbrough
Title Oil & Gas Inspector