

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
E-5841

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
Name of Operator	West Pearl Queen Unit
GULF OIL CORPORATION	8. Farm or Lease Name
Address of Operator	9. Well No.
P. O. Box 670, Hobbs, New Mexico 88240	147
1. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER <u>E</u> 1980 FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM	Pearl Queen
THE <u>West</u> LINE, SECTION <u>33</u> TOWNSHIP <u>19-S</u> RANGE <u>35-E</u> N.M.P.M.	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3719' GL	Lea

10. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK	<input type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

PLUG AND ABANDON	<input type="checkbox"/>
CHANGE PLANS	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

SUBSEQUENT REPORT OF:	
REMEDIAL WORK	<input type="checkbox"/>
COMMENCE DRILLING OPNS.	<input type="checkbox"/>
CASING TEST AND CEMENT JOBS	<input type="checkbox"/>
OTHER	<input type="checkbox"/>
ALTERING CASING	<input type="checkbox"/>
PLUG AND ABANDONMENT	<input type="checkbox"/>
P & A	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5036' TD

12-27-78: Ran & set 4-1/2" cement retainer @ 2540'. Squeezed below retainer with 200 sacks of Class "C" + 5# salt per sack & 2% CaCl₂. Capped retainer with 200' of cement. Tested casing to 500#; held o.k. Circulated hole with 37 barrels abandonment mud. Perforated (2) 1/2" JH @ 1602'.

12-28-78: Ran cement retainer & set @ 1556'. Cemented with 60 sacks of Class "C" cement + 5# salt per sack & 2% CaCl₂. Capped retainer with 100' of cement. Spotted cement plug from 50' to surface. Installed dry hole marker. Cleaned & cleared location.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>H. B. Liker Jr.</u>	TITLE <u>Area Engineer</u>	DATE <u>01-03-79</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>OIL & GAS INSPECTOR</u>	DATE <u>JUN 11 1980</u>
CONDITIONS OF APPROVAL, IF ANY:		