

DUPLICATE

RECEIVED  
SEP 16 1949

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes must be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Dallas, Texas

Sept. 14, 1949

Place

Date


OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Edwin B. Cox & Jake L. Hamon State Well No. 1 in NWNWSW  
Company or Operator Lease

of Sec. 19, T 20-S, R 35-E, N. M., P. M., Field, Lea County.



AREA 640 ACRES

LOCATE WELL CORRECTLY

The well is 2310 feet (N.) (S.) of the south line and 330 feet (E.) (W.) of the west line of Section 19

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. E-2655 Assignment No.

If patented land the owner is

Address

If government land the permittee is

Address

The lessee is Ernest A. Hanson

Address Roswell, New Mexico

We propose to drill well with drilling equipment as follows:

Combination tools--Neil Wills, Garfield, NM., contractor

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: \$5000.00 one well bond attached hereto

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
8 3/4	7"	20#	new	top salt	cemented	50
10	10 3/4"		new	1700', approx	cemented	50
7"	5 1/2"		new	3750'	cemented	100

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 3800 feet.

Additional information:

Propose to drill with rotary to base of salt and set 7" at top of salt, then finish with cable tools to approximately 3800'

Approved SEP 16 1949 19

except as follows:

Sincerely yours,

Edwin B. Cox & Jake L. Hamon

Company or Operator

By *[Signature]*

Position Agent

Send communications regarding well to

Name SAME

Address Box 627, Dallas, Texas.

OIL CONSERVATION COMMISSION

By *[Signature]*

Title GAS INSPECTOR