

State K11-12 No. 1
Proposed P & A.

sect. 12, T-19S, R36E
660' FSL & 660' FEL
Elevation - 3733 D.F.

Welded metal cap

circ. 150 sx. cmt. down casing & up csg.-csg. annulus

9 5/8", 36#/ft. csg. @ 295' w/ 200 sx. circ. to sfc.

Perf. @ 355'

Mud - (25 sx Bentonite gel per 100 bbls. brine)

T. Salt & T.D.C. (calculated) @ 1722'

Cement plug from 1800' - 1650' w/ 50 sx. cmt.

Mud - (25 sx. Bentonite gel per 100 bbls. brine water)

B. Salt @ 2652'

Cement plug from 2730' - 2580' w/ 50 sx. cmt.

Mud - (25 sx. Bentonite gel per 100 bbls. brine water)

cement retainer @ 3400' squeeze w/ 150 sx. cmt.

Spot 5 sx. cmt. above retainer

7", 20#/ft. csg. @ 3490' w/ 400 sx. cmt.

Eumont Queen O.H. section 3490' - 3826'

P.B.T.D. @ 3826'

Calseal plug @ 3626' - 3848'

Open hole bridge plug @ 3848'

Heavy Mud

T.D. - 4170'

MADE BY 581
CHECKED BY
DATE 7/12/72
PAGE

CONTINENTAL OIL COMPANY
CALCULATION SHEET

JOB No Completed 2/13/53

TITLE State K11-12 No. 1
Proposed P & A.

FIELD Eunice Monument
Lea County, NM

RECEIVED

AUG 1 1978

OIL CONSERVATION COMM
HOBBBS. H. M.