YEW MEXICO OIL CONSERVATION CAMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Wink, Texas, May 26, 1936 Place Date L CONSERVATION COMMISSION, inta Fe, New Mexico. Pollowing is a notice of intention to do certain work as described below at the State "J" Company or Operator State "J" Company or Operator Sec. 24 , T. 19 S , R. 36 E , N. M. P. M., Monument Field, Leas County. FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION T.D. 3750' Hard gray lime. Set and cemented 3735' of 7" OD 24# 10thd Seamless casing at 3750' with 400 sacks Trinity common cement. Completed cementing 8AM	COMPANY OF THE PROPERTY OF THE	ate nature of notice	by checking belo	ow:	
OTICE OF INTENTION TO CHANGE PLANS OTICE OF INTENTION TO REPAIR WELL Wink, Texas, May 26, 1936 Place Date L CONSERVATION COMMISSION, mata Fe, New Mexico. Plouding is a notice of intention to do certain work as described below at the the tense. State "J" Company or Operator Sec. 24 , T. 19 S , R. 36 E , N. M. P. M. Monument Field, Leas County. FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION T.D. 3750' Hard gray lime. Set and cemented 3735' of 7" OD 24# 10thd Seamless casing at 1750' with 400 sacks Trinity common cement. Completed cementing 8AM Will drill plug and test casing by pressure method at 8AM 5-30-36. Will drill plug and test casing by pressure method at 8AM 5-30-36.	TICE OF INTENTION TO TEST CASING SHUT-OFF X NOTICE C		F INTENTION TO SHO	OOT OR	
Wink, Texas, May 26, 1936 Place Date L CONSERVATION COMMISSION, inta Fe, New Mexico. Settlemen: Company or Operator Sec. 24 , T. 19 S , R. 36 E , N. M. P. M. Monument Field, Lease FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION T.D. 3750' Hard gray lime. Set and cemented 3735' of 7" OD 24# 10thd Seamless casing at 1750' with 400 sacks Trinity common cement. Completed cementing 8AM 1-26-36. Will drill plug and test casing by pressure method at 8AM 5-30-36.	CICE OF INTENTION TO CHANGE PLANS NOTICE O		OF INTENTION TO PULL OR		
Wink, Texas, May 26, 1936 Place Date L CONSERVATION COMMISSION, inta Fe, New Mexico. Intellemen: Company or Operator Sec. 24	OTICE OF INTENTION TO REPAIR WELL	AIR WELL NOTICE OF		' INTENTION TO PLUG WELL	
L CONSERVATION COMMISSION, and a Fe, New Mexico. Sentlemen: Dilowing is a notice of intention to do certain work as described below at the THE TEXAS COMPANY State "J" Well No. 1 in NEt of State "J" No. 24 in Nonument Field, Lea County. FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION T.D. 3750' Hard gray lime. Set and cemented 3735' of 7" OD 24# 10thd Seamless casing at 1750' with 400 sacks Trinity common cement. Completed cementing SAM 1726-36. Will drill plug and test casing by pressure method at SAM 5-30-36.	NOTICE OF INTENTION TO DEEPEN WELL				
L CONSERVATION COMMISSION, inta Fe, New Mexico. Sentlemen: Company or Operator Lease Sec. 24 , T. 19 S , R 36 E , N. M. P. M., Monument FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION T.D. 3750' Hard gray lime. Set and cemented 3735' of 7" OD 24# 10thd Seamless casing at 2750' with 400 sacks Trinity common cement. Completed cementing SAM 5-26-36. Will drill plug and test casing by pressure method at SAM 5-30-36.		Wi	nk, Texas,	May 26, 1936	<u> </u>
entlemen: State "J" Well No. 1 In NE of State "J" Well No. 1 In			Place		Date
State "J" Company or Operator Sec. 24 , T. 19 S , R. 36 E , N. M. P. M., Monument Field, Leas County. FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION T.D. 3750' Hard gray lime. Set and cemented 3735' of 7" OD 24# 10thd Seamless casing at 3750' with 400 sacks Trinity common cement. Completed cementing 8AM 5-26-36. Will drill plug and test casing by pressure method at 8AM 5-30-36.	OIL CONSERVATION COMMISSION, anta Fe, New Mexico.				
State "J" Company or Operator Lease Sec. 24	entlemen:				
Sec. 24 , T. 19 S , R. 36 E , N. M. P. M. Monument Field, Lea County. FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION T.D. 3750' Hard gray lime. Set and cemented 3735' of 7" OD 24# lothd Seamless casing at 1750' with 400 sacks Trinity common cement. Completed cementing 8AM 1-26-36. Will drill plug and test casing by pressure method at 8AM 5-30-36.	ollowing is a notice of intention to do certa	in work as describ	ed below at the	THE TEXAS C	OMPANY
Sec. 24 , T. 19 S , R. 36 E , N. M. P. M. Monument Field, Lea County. FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION T.D. 3750' Hard gray lime. Set and cemented 3735' of 7" OD 24# lothd Seamless casing at 1750' with 400 sacks Trinity common cement. Completed cementing 8AM 1-26-36. Will drill plug and test casing by pressure method at 8AM 5-30-36.	Sta	State "I"			NET of SW
FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION T.D. 3750' Hard gray lime. Set and cemented 3735' of 7" OD 24# 10thd Seamless casing at 4750' with 400 sacks Trinity common cement. Completed cementing SAM 5-26-36. Will drill plug and test casing by pressure method at SAM 5-30-36.	Company or Operator	pany or Operator Lease			1n 2124 02 04
FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION T.D. 3750' Hard gray lime. Set and cemented 3735' of 7" OD 24# 10thd Seamless casing at 3750' with 400 sacks Trinity common cement. Completed cementing 8AM 3-26-36. Will drill plug and test casing by pressure method at 8AM 5-30-36.	f Sec. 24 , T. 19 S, R.	36 E , N.	M. P. M.,	Monument	Field,
FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION T.D. 3750' Hard gray lime. Set and cemented 3735' of 7" OD 24# 10thd Seamless casing at 3750' with 400 sacks Trinity common cement. Completed cementing 8AM 3-26-36. Will drill plug and test casing by pressure method at 8AM 5-30-36.	Las	v			
T.D. 3750' Hard gray lime. Set and cemented 3735' of 7" OD 24# 10thd Seamless casing at 1750' with 400 sacks Trinity common cement. Completed cementing 8AM 15-26-36. Will drill plug and test casing by pressure method at 8AM 5-30-36.	Councy	, .			
T.D. 3750' Hard gray lime. Set and cemented 3735' of 7" OD 24# 10thd Seamless casing at 5750' with 400 sacks Trinity common cement. Completed cementing SAM 5-26-36. Will drill plug and test casing by pressure method at SAM 5-30-36.	FULL DETAI	ILS OF PROPO	SED PLAN OF	F WORK	
Set and cemented 3735' of 7" OD 24# 10thd Seamless casing at 5750' with 400 sacks Trinity common cement. Completed cementing SAM 5-26-36. Will drill plug and test casing by pressure method at SAM 5-30-36.	FOLLOW INSTRUCTIONS I	IN THE RULES AN	D REGULATIONS	OF THE COMMISSION	1
Set and cemented 3735' of 7" OD 24# 10thd Seamless casing at 5750' with 400 sacks Trinity common cement. Completed cementing SAM 5-26-36. Will drill plug and test casing by pressure method at SAM 5-30-36.					
Set and cemented 3735' of 7" OD 24# 10thd Seamless casing at 5750' with 400 sacks Trinity common cement. Completed cementing SAM 5-26-36. Will drill plug and test casing by pressure method at SAM 5-30-36.					
750' with 400 sacks Trinity common cement. Completed cementing SAM 5-26-36. Will drill plug and test casing by pressure method at SAM 5-30-36.		lime.			
-26-36. Will drill plug and test casing by pressure method at SAM 5-30-36.	T.D. 3750' Hard gray		//	_	
Will drill plug and test casing by pressure method at SAM 5-30-36.	Set and cemented 3735	5' of 7" OD	24# 10thd	Seamless cas	sing at
	Set and cemented 3735 3750' with 400 sacks Trini	5' of 7" OD	24# 10thd cement. C	Seamless cas ompleted ceme	sing at enting SAM
	Set and cemented 3735 3750' with 400 sacks Trini	5' of 7" OD	24# 10thd cement. C	Seamless cas	sing at enting 8AM
	Set and cemented 3735 3750' with 400 sacks Trini 5-26-36.	5' of 7" OD ity common	cement. C	ompleted ceme	enting 8AM
	Set and cemented 3735 3750' with 400 sacks Trini 5-26-36.	5' of 7" OD ity common	cement. C	ompleted ceme	enting 8AM
	Set and cemented 3735 3750' with 400 sacks Trini 5-26-36.	5' of 7" OD ity common	cement. C	ompleted cemer	enting 8AM 8AM 5-30-36.

Approved 1936 19 THE TEXAS COMPANY
except as follows:

Company or Operator
By

Position District Superintendent
Send communications regarding well to

The Texas Company

OIL CONSERVATION COMMISSION,
By

Gas inspector

Title Gas inspector

 $V_{ij} = V_{ij} V_{ij} + V_{ij} V_{ij} + V_{ij} V_{ij} V_{ij} V_{ij} V_{ij} + V_{ij} V_$

and the second of the second o

Lower State of the Control of the Co

garan kerangan pengangan dalam

(x,y) = (x,y) + (x,y

Committee of the Commit

30...

a Page Area Area a Market Area Area