

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION P.O. Box 2088 Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-04057
5. Indicate Type of Lease STATE [] FEE [X]
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name NORTH MONUMENT G/SA UNIT BLOCK 9
8. Well No. 12
9. Pool name or Wildcat EUNICE MONUMENT G/SA

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE 'APPLICATION FOR PERMIT' (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL [X] GAS WELL [] OTHER []
2. Name of Operator AMERADA HESS CORPORATION
3. Address of Operator DRAWER D, MONUMENT, NM 88265
4. Well Location

Unit Letter L : 660 Feet From The WEST Line and 1980 Feet From The SOUTH Line

Section 25 Township 19S Range 36E NMPM LEA County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK [] PLUG AND ABANDON [] TEMPORARILY ABANDON [] CHANGE PLANS [] PULL OR ALTER CASING [] OTHER: []
SUBSEQUENT REPORT OF: REMEDIAL WORK [] ALTERING CASING [] COMMENCE DRILLING OPNS. [] PLUG AND ABANDONMENT [] CASING TEST AND CEMENT JOB [] OTHER: TESTED CSG. & CHANGED WELL STATUS TO [X] TA'D

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 6-7 THRU 6-9-93

MIRU X-PERT WELL SER. PULLING UNIT. REMOVED 6" 900 DOUBLE DRILLED FLANGE & INSTALLED A 6" 600 MANUAL BOP & TOH WITH 2-3/8" TBG. TIH WITH A 6-1/8" BIT. TAGGED AT 3,802' & TOH. TIH WITH A 5.5." ELDER CAST IRON BRIDGE PLUG. SET AT 3660'. PRESS. TESTED 7" CASING FROM 0' TO 3,660'. PRESSURE DECREASED FROM 540 PSI TO 525 PSI IN 30 MINUTES. CHECKED SURFACE-INTERMEDIATE CASING ANNULUS AND FOUND 0 PSI. FLOWED GAS FROM ANNULUS FOR AN INSTANT AND FLOW CEASED. CHECKED INTERMEDIATE-PRODUCTION CASING ANNULUS AND FOUND 400 PSI. FLOWED OIL & GAS FROM ANNULUS FOR 30 MIN. AND FLOW CEASED. CIRC. CASING WITH 150 BBLs. PACKER FLUID AND TOH LAYING DOWN 2-3/8" TBG. LOADED CSG. WITH PACKER FLUID, REMOVED 6" 600 MANUAL BOP & INSTALLED A 6" 600 FLANGE HALF. RIGGED DOWN PULLING UNIT, CLEANED LOCATION & TA'D WELL.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE [Signature] TITLE SUPV. ADMIN. SER. DATE 7-13-93 TYPE OR PRINT NAME ROY L. WHEELER, JR. TELEPHONE NO. 393-2144

(This space for State Use) ORIGINAL SIGNED BY JERRY SEXTON DISTRICT I SUPERVISOR APPROVED BY [Signature] TITLE DATE JUL 16 1993

CONDITIONS OF APPROVAL, IF ANY: This Approval of Temporary Abandonment Expires 7-1-98

RECEIVED

JUN 15 1992

LIBRARY OF THE
CONGRESS

UNIVERSITY OF MICHIGAN LIBRARY