

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	18	18	Cellar and sub structure.
18	153	135	Sand and rock.
153	206	53	Red Beds. (set 12 1/2" Csg. at 198' with 150 sx. cement.)
206	350	144	Red Beds and shells.
350	1125	775	Red Rock.
1125	1135	10	Anhydrite and Red Rock. (Top Anhydrite.)
1135	1240	95	Anhydrite.
1240	2257	1017	Anhydrite and salt.
2257	2285	28	Anhydrite.
2285	2390	105	Anhydrite and salt and shell.
2390	2419	29	Anhydrite and salt (base of the salt.)
2419	2470	49	Anhydrite. (set 9-5/8" csg. at 2470' with 500 sx. cement.)
2470	2472		Steel line correction.
2472	2620	148	Anhydrite.
2620	2650	30	Anhydrite and streaks of lime.
2650	2865	215	Lime.
2865	2915	50	Anhydrite and lime.
2915	3000	85	Lime.
3000	3030	30	Lime and broken Anhydrite.
3030	3045	15	Lime.
3045	3083	38	Broken lime.
3083	3236	153	Lime.
3236	3276	40	Gray Lime.
3276	3368	92	Lime.
3368	3382	14	Lime. (small show of gas at 3370')
3382	3514	132	Lime.
3514	3542	28	Lime. (small show of gas at 3519-3530.)
3542	3670	128	Lime.
3670	3682	12	Sandy Lime.
3682	3834	152	Lime. (7" Csg. set at 3832 with 100 sx. 2-27-36.)
3834	3837	3	Straight rearing. (started drilling cable tools.) 5-11-36.
			Lime.
3837	3842	5	Lime.
3842	3860	18	Hard gray lime.
3860	3875	15	Gray Lime. (increase in oil and gas at 3860-3865)
3875	3940	65	Lime.
3940	3937		Steel line correction.
3937	3944	7	Lime (acidizing with 4000 gal. at 3959)
3944	3953	8	Lime
3953	3959	6	Lime (acidized with 2000 gal.)
3959	3962	3	Lime
3962	3968	6	Lime
3968	3972	4	Lime (Bailed down at 3972 1 bailer per hour.)
3972	3990	18	Lime (Steel line correction 3972-3980)
3990	4001	11	Lime
	Plugging back		
4001	3996	5	Plugged with lead wool
3996	3965	31	Plugged with gravel
3965	3962	3	Plugged with steel cuttings.
3962	3951	11	Plugged with lead wool
3951	3910	41	Plugged with gravel.
3910	3905	5	Plugged with steel cuttings.
3905	3897	8	Plugged with lead wool.
			Shot well with 75 Gts. from 3840-3897 date 4/11/36.
			Clean down to 3897'
			20 hour test 113 bbls.