

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Skelly Oil Company

A. L. Christmas

Company or Operator _____ Well No. 1 in CSW/4, SW/4 of Sec. 25, T. 19S
R. 36E, N. M. P. M., Monument Field, Lea County.
Well is 660 feet south of the North line and 660 feet west of the East line of Section
If State land the oil and gas lease is No. _____ Assignment No. _____
If patented land the owner is Anna L. Christmas, Address Hobbs, New Mexico
If Government land the permittee is _____, Address _____
The Lessee is Skelly Oil Company, Address Box 1650, Tulsa, Oklahoma
Drilling commenced February 24, 19 36 Drilling was completed April 9, 19 36
Name of drilling contractor Davidson Drilling Company, Address Fort Worth Texas
Elevation above sea level at top of casing 3621 feet.
The information given is to be kept confidential until _____, 19 _____

OIL SANDS OR ZONES

No. 1, from 3802 to 3805 No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.
No. 2, from _____ to _____ feet.
No. 2, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WRIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13" OD	45#	8	LW	280'				
9 5/8"	36#	8	SS	1199'	Larkin			
7" OD	24#	10	SS	3790'				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15"	13"	280'	290	Halliburton		
11"	9-5/8"	1199'	300	Halliburton		
8-1/4"	7"	3790'	300	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Acid (50%)	1000 gals.	4-11/36	3935	Swabbed T.D.
3-1/2"	Tin	S. N. G.	200 qts.	4-14/36	3942'-3957'	T.D.
		Acid (50%)	4000 gals	4-21-36	3942	Swabbed, T.D.

Results of shooting or chemical treatment after first acid treatment, well swabbed approximately 60 bbls oil in 24 hours. After shot, hole temporarily bridged but later cleaned self and flowed approximately 130 bbls into tanks and pits. Swabbed and flowed 110 bbls after third acid shot.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3792' feet, and from _____ feet to _____ feet
Cable tools were used from 3792' feet to 3935' feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing April 25, 19 36
The production of the first 24 hours was 110 barrels of fluid of which 100 % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be _____
If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. _____

EMPLOYEES

G. O. Lambert, Driller O. C. Robinson, Driller
S. W. Ferrell, Driller W. G. Suppers, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 28day of Apr, 19 36Patricia Mahoney
Notary Public.My Commission expires 10-24-39Hobbs, New Mexico April 27, 1936
Place DateName J. T. DunawayPosition District SuperintendentRepresenting Skelly Oil Company
Company or OperatorAddress Drawer "D", Hobbs, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	91	91	Caliche
91	515	424	Red Bed, Sand, Shells
515	1035	520	Red Rock, Red Bed, Shells, Anhydrite
1035	1197	162	Anhydrite, Gyp Shells, Red Rock
1197	2490	1293	Salt, Shells, and Anhydrite
2490	2897	407	Lime and Anhydrite
2897	2933	141	Lime and Sand
2938	3538	600	Lime
3538	3627	89	Brown Lime
3627	3802	175	Grey Lime
3802	3935	133	Pay