

NEW MEXICO OIL CONSERVATION COMMISSION

Header section with fields for well name, location, and company. Includes 'DUPLICATE' stamp.

Well location and ownership details. Includes 'Sun Oil Company' and 'State of N. Mexico'.

Drilling and casing records. Includes 'Drilling commenced April 27' and 'Casing Record' table.

Table with columns: SIZE, WEIGHT PER FOOT, THREADS PER INCH, MAKE, AMOUNT, KIND OF CUT & FILLED FROM, PERFORATED FROM TO, PURPOSE.

Table with columns: SIZE OF HOLE, SIZE OF CASING, WHERE SET, NO. SACKS OF CEMENT, METHOD USED, MUD GRAVITY, AMOUNT OF MUD USED.

PLUGS AND ADAPTERS section with fields for material, length, and depth.

Table with columns: SIZE, SHELL USED, EXPLOSIVE OR CHEMICAL USED, QUANTITY, DATE, DEPTH SHOT OR TREATED, DEPTH CLEANED OUT.

Results of shooting or chemical treatment: After flowing in pit for 4 hrs. after treating, flowed 80 bbls. 5th hr. and 69 bbls. 6th hr. in tank.

RECORD OF DRILL-STEM AND SPECIAL TESTS. If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED section with fields for rotary and cable tools.

PRODUCTION section with fields for start date, production volume, and gas pressure.

EMPLOYEES section listing Cecil Watson, Ray Hill, L. O. Ward, and C. B. Fugitt.

FORMATION RECORD ON OTHER SIDE. I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Notary and signature section. Includes 'Subscribed and sworn to before me this 17th day of June, 1936' and signature of John A. Ritter.

FORMATION RECORD

FORM 0-105

FROM	TO	THICKNESS IN FEET	FORMATION
0	40	40	Caliche
40	82	22	Sand & gravel
82	300	238	Red beds & boulders.
300	312	12	Red rock & red beds.
312	528	214	Red beds & boulders.
528	630	104	Red bed & shells
630	712	82	Red bed & red rock
712	732	20	Sticky red beds
732	780	48	Red bed & shells
780	805	25	Red rock, shale & shells
805	846	41	Shale & Shells
846	862	16	Red bed.
862	884	22	Red rock & shells
884	989	105	Shale & shells
989	1028	39	Red rock & shale
1028	1100	72	Red rock & shells
1100	1162	62	Hard sand, shale & shells
1162	1217	55	Hard red rock
1217	1248	31	Red rock & shale
1248	1288	40	Brown shale, gypsum & lime shells.
1288	1315	27	Lime & strks anhydrite
1315	1358	43	Salt & anhydrite
1358	1479	121	Anhydrite, red rock & salt strks.
1479	1682	203	Anhydrite, shale & salt
1682	1682	0	Broken salt & anhydrite
1682	1671	11	Anhydrite
1671	1700	29	Potash, shale & salt.
1700	1715	15	Anhydrite
1715	1746	31	Shale & salt
1746	1760	14	Potash, shale & salt
1760	1775	15	Anhydrite
1775	1800	25	Salt & shale
1800	1820	20	Salt, potash & anhydrite.
1820	1820	0	Anhydrite
1820	1910	90	Salt & strks anhydrite.
1910	1922	12	Hard anhydrite
1922	1955	33	Salt & potash
1955	2098	143	Salt & anhydrite
2098	2110	12	Anhydrite
2110	2159	49	Anhydrite, potash & salt
2159	2376	217	Salt & strks anhydrite.
2376	2427	51	Salt
2427	2448	21	Anhydrite
2448	2462	14	Anhydrite
2462	2469	7	Salt
2469	2470	1	Anhydrite
2470	2478	8	Salt
2478	2550	72	Salt & anhydrite
2550	2577	27	Anhydrite
2577	2713	136	Anhydrite & gypsum
2713	2758	45	Anhydrite
2758	2803	45	Anhydrite & gypsum.
2803	2838	35	Anhydrite.
2838	2897	59	Anhydrite & strks, brown lime
2897	3072	175	Lime w/ strks. shale
3072	3153	81	Anhydrite
3153	3159	6	Broken lime (Gas show)
3159	3159	0	Anhydrite & strks, gypsum.
3159	3209	50	Lime
3209	3303	94	Anhydrite & lime
3303	3419	116	Lime
3419	3468	49	Lime & strks. of anhy. & gypsum.
3468	3714	246	Lime
3714	3748	34	Lime w/ strks shale
3748	3859	111	Lime
3859	3904	45	Lime w/ small oil show
3904	3988	84	Lime
	3988	TOTAL DEPTH.	