


# OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS



DUPLICATE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission. Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL	<b>X</b>	

February 5, 1950

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
**Amerada Petroleum Corporation** H. S. Record "A" Well No. 1 in the \_\_\_\_\_  
 Company or Operator  
C/NW/4 NW/4 of Sec. 33, T. 19-S, R. 36-E, N. M. P. M.,  
**West Flank Monument Area** Field, Lea County.

The dates of this work were as follows: February 4, 1950

Notice of intention to do the work was ~~(submitted)~~ submitted on Form C-102 on February 4, 19 50  
 and approval of the proposed plan was ~~(obtained)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

**6971' - Total Depth - Line.** Ram Schlumberger's Electrical & Gamma Ray Surveys. Heavy mud from 6971' to 5300', spotted 35 sacks of Lone Star cement from 5300' to 5146', heavy mud from 5146' to 3339', spotted 35 sacks of Lone Star cement from 3339' to 3185'. Shot off 8-5/8" casing and recovered 2178' (shot casing off at 2191'). Heavy mud from 3185' to 1800', spotted 30 sacks cement from 1800' to 1700', heavy mud from 1700' into surface casing and spotted 25 sacks of Lone Star cement on top of mud to top of surface casing. Set a piece of 4" Line Pipe, cemented in center of the surface casing, 5' above surface of the ground. Finished at 3:30 P.M., February 4, 1950.

Witnessed by Don Tepper Amerada Petroleum Corporation Assistant Dist. Supt.  
 Name Company Title

Subscribed and sworn before me this \_\_\_\_\_  
6th day of February 19 50  
  
 Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name Don Tepper  
 Position Assistant District Superintendent  
 Representing Amerada Petroleum Corporation  
 Company or Operator

My commission expires 10-24-53

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Date FEB 9 1950

Name \_\_\_\_\_  
 Title \_\_\_\_\_