

Confidential

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

DUPLICATE
MISCELLANEOUS REPORTS ON WELLS

RECORDED
DEC 26 1947
REGISTRY
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Squeezing Well	X

December 23, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Confidential

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation

J. R. Phillips

Well No. 5

in the _____

Company or Operator

Lease

NE 1/4 NE 1/4

of Sec. 1

T. 20S

R. 36E

N. M. P. M.,

Monument

Field, Lea

County.

The dates of this work were as follows: December 22, 23, 1947

Notice of intention to do the work was (~~received~~) submitted on Form C-102 on December 22, 19 47

and approval of the proposed plan was (~~received~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

5611' Retainer Depth. Set Baker Model K Cement Retainer at 5611' and pumped 12 bbls. water into formation with 1300#. Squeezed with 50 sacks of Lone Star Common Cement with 38 sacks going into formation with 4100# pressure and 2000# on casing. Reversed out 10 sacks cement. Perforated with Lane Wells from 5600' to 5610', 40 holes. Displaced water with 130 bbls. oil and set packer at 5568' with 1-2' perf. nipple on bottom of tubing at 5606'. Started swabbing and in 9 hours recovered 32 bbls. load oil.

Witnessed by W. D. Jarred

Amerada Petroleum Corporation

Farm Boss

Name

Company

Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

2rd day of December, 19 47

Name [Signature]

Will Haile Taylor
Notary Public

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires My Commission Expires May 31, 1953

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Date DEC 23 1947

[Signature]
Name
OIL & GAS INSPECTOR
Title