

DUPLICATE
OIL CONSERVATION COMMISSION
Santa Fe, New Mexico
MISCELLANEOUS REPORTS ON WELLS

RECEIVED
DEC 3 1947
RECEIVED
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report of Plugging Back	X

November 25, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the
Amerada Petroleum Corporation J. R. Phillips Well No. 5 in the
Company or Operator Lease
NE 1/4 NE 1/4 of Sec. 1, T. 20S, R. 36E, N. M. P. M.,
Monument Field, Lea County.

The dates of this work were as follows: November 24, 25 - 1947

Notice of intention to do the work was (~~was~~) submitted on Form C-102 on November 24, 19 47
and approval of the proposed plan was (~~was~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

7099' Plugged Back Depth, 7119' Drilled Out Depth. Ran Baker Bridging Plug and set at 7170'. Dumped 20 sacks of Incor Cement on top of plug, pulled up and reversed out about 8 sacks of cement. Drilled out cement from 7099' to 7119' and perforated with Lane Wells from 7070' to 7110', 240 shots. Ran 2-7/8" OD Hydril Speedtite Tubing and American Packer with Packer swung at 7040' and 1-2' perf. sub on bottom of tubing at 7111'.

Witnessed by W. D. Jarred Amerada Petroleum Corporation Farm Boss
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

25th. day of November, 19 47

Name _____

Will Hale Jarred
Notary Public

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED
DEC 3 1947

Date _____

Roy Garberoff
Name
OIL & GAS INSPECTOR

Title