


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

DUPLICATE MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

Table with 4 rows and 2 columns for reporting categories: REPORT ON BEGINNING DRILLING OPERATIONS, REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL, REPORT ON RESULT OF TEST OF CASING SHUT-OFF, REPORT ON RESULT OF PLUGGING OF WELL; and REPORT ON REPAIRING WELL, REPORT ON PULLING OR OTHERWISE ALTERING CASING, REPORT ON DEEPENING WELL.

November 15, 1947 Monument, New Mexico

Date Place

OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Amerada Petroleum Corporation J. R. Phillips Well No. 5 in the

Company or Operator Lease 20S Well No. 5 in the NE 1/4 NE 1/4 of Sec. 1, T. 20S, R. 36E, N. M. P. M., Monument Field, Lea County.

The dates of this work were as follows: November 6 to 15, 1947

Notice of intention to do the work was submitted on Form C-102 on November 2, 1947 and approval of the proposed plan was obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

9953' Total Depth, Granite, 7710' Drilled Out Depth. Nippled up 5 1/2" Casing, drilled out cement from 3940' to 7710' and tested casing with 1000# for 30 minutes before and after drilling cement and was OK. Ran Lane Wells Neutron Survey and Amerada GRC Surveys. Perforated with Lane Wells from 7665' to 7690', 100 holes. Ran American Hook Wall Packer and 246 joints of 2" EUE, 4.7#, J-55, R-2, 8-RT, SS Tubing New with Packer set at 7656' and 1-2' perforated sub on bottom of tubing at 7690'. In 15 hours swabbed 17.25 bbls. of oil to tanks, 3.2% BS, 2.4% water. Pulled tubing and perforated with Lane Wells from 7645' to 7665', 80 holes. Ran tubing back in with Packer at 7621' and 2' perf. sub on bottom of tbg. at 7690'.

Witnessed by D. F. Furse Amerada Petroleum Corporation Foreman

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

15th day of November, 1947

Name Don Phillips

Will Ailes Taylor Notary Public

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation Company or Operator

My commission expires My Commission Expires May 4, 1948

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

NOV 21 1947

Roy Gardner Name

OIL & GAS INSPECTOR Title