

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

DUPLICATE MISCELLANEOUS REPORTS ON WELLS

RECEIVED JUL 10 1947 HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

Table with 4 rows and 2 columns of report categories. The first column lists: REPORT ON BEGINNING DRILLING OPERATIONS, REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL, REPORT ON RESULT OF TEST OF CASING SHUT-OFF, REPORT ON RESULT OF PLUGGING OF WELL. The second column lists: REPORT ON REPAIRING WELL, REPORT ON PULLING OR OTHERWISE ALTERING CASING, REPORT ON DEEPENING WELL, Report on Setting Casing (checked with X).

July 5, 1947 Date Monument, New Mexico Place

OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO. Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Amerada Petroleum Corporation J. R. Phillips Well No. 5 in the Company or Operator Lease

SE 1/4 of Sec. 1, T. 20 S., R. 36 E., N. M. P. M., Monument, Lea County.

The dates of this work were as follows: July 4, 1947

Notice of intention to do the work was (was not) submitted on Form C-102 on July 2, 1947 and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

5121' Total Depth Line, Ran 20 Jts 8 5/8" OD 36#, N-80, R-3, Pittsburg Seamless and 82 Jts 8 5/8" OD 36#, J-55, J&L Seamless Steel and 44 Jts 8 5/8" OD 32#, J-55, R-3, 8 RT J&L Seamless Steel Casing total of 146 Jts and set at 5121' and cemented with 1000 Sacks El Toro Common 2% Howcogel, and 200 Sacks El Toro Common and 50 Sacks Incor and plug pumped to 5047' at 9:35PM, Final Pressure 1300#.

Witnessed by Ray Siefert Name Amerada Pet. Corp. Asst. Dist. Supt. Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

5 day of July, 1947

Name [Signature]

Will Haire Taylor Notary Public

Position Asst. Dist. Supt.

Representing Amerada Pet. Corp. Company or Operator

My commission expires My Commission Expires May 5, 1948

Address Drawer D, Monument, New Mexico.

Remarks:

APPROVED

Date JUL 10 1947

Roy Yankrough Name Oil & Gas Inspector Title