NF MEXICO OIL CONSERVATION C' MISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

OTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR	
	CHEMICALLY TREAT WELL	
TICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
TICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL	
TICE OF INTENTION TO DEEPEN WELL		
<u> </u>	nk, Texas, November 27, 1935	
L CONSERVATION COMMISSION, nta Fe, New Mexico. ntlemen: llowing is a notice of intentiton to do certain work as	described below at the The Texas Company	
State "E" Company or Operator Lease	Well No. 1 in SW	
Sec. 1 , T. 20 S , R 36 E	, N. M. P. M., Monument	ield.
LeaCounty.		iciu,
D.3810' Brown & white lime. t and cemented 5" OD 18# Seamles	es and regulations of the commission as casing at 3795' with 35 sacks In 30AM 11-27-35. Halliburten method	coı
.D.3810° Brown & white lime. et and cemented 5° OD 18# Seemles ement. Completed cementing at 5:	ss casing at 3795' with 35 sacks Tr	
.D.3810° Brown & white lime. et and cemented 5° OD 18# Seemles ement. Completed cementing at 5:	es casing at 3795° with 35 sacks In 30AM 11-27-35. Halliburten method	
.D.3810° Brown & white lime. et and cemented 5° OD 18# Seemles ement. Completed cementing at 5:	es casing at 3795° with 35 sacks In 30AM 11-27-35. Halliburten method	
D.3810' Brown & white lime. It and cemented 5" OD 18# Seamles ment. Completed cementing at 5: The seamles of	as casing at 3795° with 35 sacks In:30AM 11-27-35. Halliburten method method ested by pressure/at 5:30AM 11-30-3	
D.3810' Brown & white lime. It and cemented 5" OD 18# Seamles ment. Completed cementing at 5: The seamles of	THE TEXAS COMPANY Company or Operator	
D.5810° Brown & white lime. et and cemented 5° OD 18# Seamles ment. Completed cementing at 5: aug will be drilled and casing to	THE TEXAS COMPANY Company or Operator By Division Superintendent	
D.5810° Brown & white lime. et and cemented 5° OD 18# Seamles ment. Completed cementing at 5: aug will be drilled and casing to be proved	THE TEXAS COMPANY Company or Operator By Division Superintendent Send communications regarding well to	
D.3810° Brown & white lime. et and cemented 5" OD 18# Seamles ement. Completed cementing at 5: lug will be drilled and casing to	THE TEXAS COMPANY Company or Operator By Division Superintendent Send communications regarding well to	