

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

RECEIVED
SEP 26 1947

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	Report on Setting Casing	X

September 24, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation **H. W. Andrews** Well No. **8** in the _____
Company or Operator Lease

NW 1/4 NW 1/4 of Sec. **12**, T. **20S**, R. **36E**, N. M. P. M.,
Monument Field, **Lea** County.

The dates of this work were as follows: **September 23, 1947 and September 24, 1947**

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on **September 23,** 19 **47**
and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

2359' Total Depth, Anhydrite. Ran 49 joints of 13-3/8" OD, 68#, J-55, R-2, 8-RT, Reg. T&C, Spang SS Casing New, 6 joints of 13-3/8" OD, 68#, J-55, R-2, 8-RT, Long. T&C, Spang SS Casing New and 32 joints of 13-3/8" OD, 48#, H-40, R-1&2, 8-RT, J&L SS Casing New for a total of 87 joints and set at 2324'. Cemented with 2000 sacks of El Toro Regular Cement 3% Howcogel and 500 sacks of El Toro Regular Cement and plug pumped to 2244' at 5:34AM, 9-24-47. Final pressure 900#. Cement circulated.

Witnessed by **W. D. Jarred** **Amerada Petroleum Corporation** **Farm Boss**
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

24th. day of **September**, 19 **47**

Name W. D. Jarred

Will Dale Taylor
Notary Public

Position **Asst. Dist. Supt.**

Representing **Amerada Petroleum Corporation**
Company or Operator

My commission expires _____
My Commission Expires May 9, 1948

Address **Drawer D, Monument, New Mexico**

Remarks:

Ray Yarbrough
Name
OIL & GAS INSPECTOR
Title

APPROVED

SEP 26 1947
Date