

NAME OF OPERATOR		
DEPARTMENT		
DATE		
TITLE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

CANTA FE, NEW MEXICO 87501

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
(SEE APPLICATION FOR PERMIT - ** (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL GAS WELL OTHER

Name of Operator
Amerada Hess Corporation

Address of Operator
Drawer D, Monument, New Mexico 88265

Location of Well
UNIT LETTER **J**, **1980** FEET FROM THE **South** LINE AND **1980** FEET FROM
THE **East** LINE, SECTION **12** TOWNSHIP **20-S** RANGE **36-E** N.M.P.M.

7. Unit Agreement Name

8. Farm or Lease Name
W. P. Byrd *Byrd 3*

9. Well No.
3

10. Field and Pool, or Wildcat
Eunice Monument G/SA

15. Elevation (Show whether DF, RT, GR, etc.)
3562' DF

12. County
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

December 1979

Pulled rods, pump & tbg. McCullough string shot Grayburt San Andres zone in open hole fr. 3790' to 3850' w/400 gr. per ft. Checked for fill. String shot open hole fr. 3790' to 3840' w/600 gr. per ft. Cleaned out fill in open hole fr. 3832' to 3850' w/sand pump. Ran pkr. & tbg. & Dowell acidized Grayburt San Andres zone in open hole fr. 3784' to 3850' w/6000 gal. 20% NE FE acid using rock salt and paraformaldehyde as diverter. Swabbed load. Re-ran tbg., pump and rods and resumed pumping.

Test of 12-26-79: Pumped 34 b.o. & 100 b.w. in 24 hrs. on 12-54" SPM.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *EB Fisher* TITLE Supv. Adm. Ser. DATE 12-27-79

APPROVED BY Jerry Sexton TITLE Dist 1, Supv. DATE DEC 31 1979

CONDITIONS OF APPROVAL, IF ANY