

TRIPPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

RECEIVED APR 3 1941 HOBBS OFFICE

Grid for locating well correctly

AREA 640 ACRES LOCATE WELL CORRECTLY

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE.

Guy H. Hooper

Box 733 Roswell, New Mexico

Company or Operator

Address

Record Well No. 1 in SE 1/4 of Sec. 15, T. 20 S

R. 36 E N. M. P. M. Monument Field, Lea, County.

Well is 1650 feet south of the North line and 330 feet west of the East line of Section 15

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Henry Record, Address

If Government land the permittee is, Address

The Lessee is, Address

Drilling commenced Jan. 21, 1940 19 Drilling was completed Jan. 27, 1940,

Name of drilling contractor Two States Drilling Co., Address Hobbs, New Mexico

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

Table with columns: SIZE, WEIGHT PER FOOT, THREADS PER INCH, MAKE, AMOUNT, KIND OF SHOE, CUT & FILLED FROM, PERFORATED FROM TO, PURPOSE

MUDDING AND CEMENTING RECORD

Table with columns: SIZE OF HOLE, SIZE OF CASING, WHERE SET, NO. SACKS OF CEMENT, METHOD USED, MUD GRAVITY, AMOUNT OF MUD USED

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

Table with columns: SIZE, SHELL USED, EXPLOSIVE OR CHEMICAL USED, QUANTITY, DATE, DEPTH SHOT OR TREATED, DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 1300 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 19
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

A. L. Rodgers, Driller Clyde Waughman, Driller
R. D. Nichols, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 10th day of March 1941 at Dallas, Texas. Notary Public
Name W. K. Powell Position
Date 3-10-41

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	120	120	Surface Caliche & Sand
121	270	150	Hard Sand
271	1216	946	Red Beds
1217	1240	24	Salt Anhydrite
1241	1301	61	Anhydrite
		1301	

NEW MEXICO
OIL CONSERVATION COMMISSION
MAR 18 1941