



**RECORD OF DRILL-STEM AND SPECIAL TESTS**

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

**TOOLS USED**

Rotary tools were used from 0 feet to 1528 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.  
 Cable tools were used from 1528 feet to 4030 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.

**PRODUCTION**

Put to Producing Dry Hole, 19\_\_\_\_

OIL WELL: The production during the first 24 hours was \_\_\_\_\_ barrels of liquid of which \_\_\_\_\_% was  
 was oil; \_\_\_\_\_% was emulsion; \_\_\_\_\_% water; and \_\_\_\_\_% was sediment. A.P.I.  
 Gravity \_\_\_\_\_

GAS WELL: The production during the first 24 hours was \_\_\_\_\_ M.C.F. plus \_\_\_\_\_ barrels of  
 liquid Hydrocarbon. Shut in Pressure \_\_\_\_\_ lbs.

Length of Time Shut in \_\_\_\_\_

**PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):**

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy. <u>1990</u>	_____	T. Devonian	_____
T. Salt <u>2120</u>	_____	T. Silurian	_____
B. Salt <u>3440</u>	_____	T. Montoya	_____
T. Yates <u>3666</u>	_____	T. Simpson	_____
T. 7 Rivers <u>3775</u>	_____	T. McKee	_____
T. Queen <u>4022</u>	_____	T. Ellenburger	_____
T. Grayburg	_____	T. Gr. Wash	_____
T. San Andres	_____	T. Granite	_____
T. Glorieta	_____	T. _____	_____
T. Drinkard	_____	T. _____	_____
T. Tubbs	_____	T. _____	_____
T. Abo	_____	T. _____	_____
T. Penn	_____	T. _____	_____
T. Miss	_____	T. _____	_____
T. Ojo Alamo	_____	T. Kirtland-Fruitland	_____
T. Farmington	_____	T. Pictured Cliffs	_____
T. Menefee	_____	T. Point Lookout	_____
T. Mancos	_____	T. Dakota	_____
T. Morrison	_____	T. Penn	_____
T. _____	_____	T. _____	_____
T. _____	_____	T. _____	_____
T. _____	_____	T. _____	_____

**FORMATION RECORD**

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1990	1990	Red Sand and Shale				
1990	2120	130	Anhy.				
2120	3440	1320	Salt W/stringers of Anhy.				
3440	3666	226	Anhy. W/stringers of Dolo.				
3666	3775	109	Sand W/some Anhy.				
3775	3910	135	Anhy. W/stringers of Sand & Dolo.				
3910	3998	88	Sand W/some Dolo.				
3998	4022	24	Dolo.				
4022	4030	8	Sand				
Hole full water.							
Hole plugged and abandoned in accordance with rules and regulations and Stafforders Hobbs Office of New Mexico Oil Conservation Commission.							

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

2-2-55

Company or Operator Cactus Drilling Co.  
 Name [Signature]

(Date)  
 Address Box 348, San Angelo, Texas  
 Position or Title Office Manager