

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

LC 030143B ✓

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Reed B No. 6 ✓

9. API Well No.

300250429900

10. Field and Pool, or Exploratory Area

Eumont Oil

11. County or Parish, State

Lea, NM

**SUBMIT IN TRIPLICATE**

1. Type of Well

Oil Well  Gas Well  Other

2. Name of Operator

Conoco Inc.

3. Address and Telephone No.

10 Desta Drive West, Midland, TX 79705 (915) 686-6548

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

990' FSL & 1650' FEL  
Sec. 23, T-20S, R-36E

*Unit 0*

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- Notice of Intent  
 Subsequent Report  
 Final Abandonment Notice

TYPE OF ACTION

- Abandonment  
 Recompletion  
 Plugging Back  
 Casing Repair  
 Altering Casing  
 Other Squeeze Perfs.  
 Change of Plans  
 New Construction  
 Non-Routine Fracturing  
 Water Shut-Off  
 Conversion to Injection  
 Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

It is proposed to squeeze off lower Queen perforations, to prepare this well for inclusion in the expansion area to the Eunice Monument South Unit, by the following procedure:

1. RIH with bit and casing scraper to TD at 3866'.
2. Fill hole with 20/40 sand to 3673'.
3. Set cement retainer at 3535' and squeeze Queen perforations from 3553'-3667' with 250 sxs cement.
4. Drill out cement and retainer.
5. Pressure test casing to 500 psi for 30 minutes.
6. Circulate sand out of hole and clean out to TD (3852').
7. RIH with producing equipment and leave TSI pending assumption of operatorship by Chevron.

14. I hereby certify that the foregoing is true and correct

Signed Jerry W. Hoover Title Regulatory Coordinator

Date 12/4/90

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_

Date 12-6-90

THIS APPROVAL IS FOR THE PROPOSED REMEDIAL WORK.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.