

OIL CONSERVATION DIVISION

P. O. BOX 2088
 SANTA FE, NEW MEXICO 87501

Form C-103
 Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
 State Fee
 5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL GAS WELL OTHER-
 Name of Operator: **Chevron U.S.A. Inc.**
 Address of Operator: **P.O. Box 670 Hobbs, NM 88240**
 Location of Well: UNIT LETTER D, 660 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 36 TOWNSHIP 20S RANGE 36E NMPM.
 7. Unit Agreement Name: **Eunice Monument South**
 8. Farm or Lease Name: **Unit**
 9. Well No.: **141**
 10. Field and Pool, or Whitcat: **Eunice Monument G/SA**
 11. Elevation (Show whether DF, RT, GR, etc.): **3555'**
 12. County: **Lea**

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

FORM REMEDIAL WORK
 TEMPORARILY ABANDON
 OR ALTER CASING
 PLUG AND ABANDON
 CHANGE PLANS
 OTHER perf/acdz/test zones 1&2 & zone 3

SUBSEQUENT REPORT OF:

REMEDIAL WORK
 COMMENCE DRILLING OPNS.
 CASING TEST AND CEMENT JOB
 OTHER
 ALTERING CASING
 PLUG AND ABANDONMENT

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

It is proposed to perf zone 3 as follows: Perf 4" liner w/2½" guns, 1SPF 180° phase and premium charges at 3980-4008 28 holes. Spot w/100 gallons 15% NEFE HCL across perfs, follow spot w/1500 gallons 15% NEFE HCL. Swab back and report results to Production Engineer. Based on results, zone 1&2 procedure will follow.

Perf zone 1 & 2 as follows: Set CIBP at 3970'. Test same to 500psi. Perf 4" liner w/2 1/8" guns, 1 SPF, 180° phase, at 3910-24, 3931-47, 3952-60 (38 holes). Spot 100 gallons 15% NEFE HCL across perfs, follow spot w/1800 gallons 15% NEFE HCL, flush to bottom perf, swab back residue. POOH, set CIBP at 3905, perf 4" liner at 3861-67, 3870-84, 3888-3898 (zone 1) 30 holes. Spot 100 gallons 15% NEFE HCL across perfs, follow spot w/1400 gallons 15% NEFE, swab back and report results to production engineer. Remainder of procedure contingent on swab results.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

M. E. Abner TITLE: Staff Drilling Engineer DATE: June 9, 1988

ORIGINAL SIGNED BY JERRY SEXTON
 DISTRICT SUPERVISOR

TITLE: _____ DATE: _____

CONDITIONS OF APPROVAL, IF ANY: