

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.

30-025-05626

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

E-6506-1

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☐

OTHER INJECTION

2. Name of Operator

Amerada Hess Corporation

3. Address of Operator

P.O. BOX 840 SEMINOLE, TX 79363

8. Well No.

7

9. Pool name or Wildcat

EUNICE MONUMENT G/SA

4. Well Location

Unit Letter G : 1980 Feet From The NORTH Line and 1980 Feet From The EAST Line

Section

18

Township

19S

Range

37E

NMPM

LEA

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: CONVERT TO INJECTION WELL ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-10-1998 THRU 2-20-1998 DIVISION ORDER #R-9596, ADMIN. ORDER #WFX-716
MIRU TYLER WELL SVC. & TOH W/RODS & PUMP. REMOVED WELLHEAD, INSTALLED BOP & TOH W/TBG.
TIH W/4-3/4" BIT TO 3874' & TOH. TIH W/5-1/2" RBP & SET AT 3846'. DUMPED 1 SK. SAND
ON TOP RBP. REMOVED BOP & OLD WELLHEAD. INSTALLED NEW WELLHEAD. RE-INSTALLED BOP.
RAN RETRIEVING HEAD, CIRC. SAND OFF RBP, LATCHED ONTO & TOH W/RBP. RAN 4-3/4" BIT
& TAGGED AT 3874'. BROKE CIRC. & CLEANED OUT OH TO TD AT 4030'. CIRC. CLEAN. TIH
W/2-3/8" TBG. SET OE AT 4029'. HALLIBURTON SVC. SPOTTED 25 SKS. CLASS H CEMENT. WOC.
TAGGED TOP OF CEMENT AT 3969'. SWABBED WELL. WESTERN ATLAS PERF. 5-1/2" CSG. W/2 SPF,
TOTAL 53 HOLES, USING 4" PERF. GUN FR. 3846' - 3872'. AMERICAN FRACMASTER ACIDIZED PERFS.
FR. 3846' - 3872' & O.H. FR. 3874' - 3969' W/4200 GAL. 15.5% NEFE ACID.

CONTINUED OVER.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Colleen Robinson

TITLE Staff Assistant

DATE 2-26-98

TYPE OR PRINT NAME Colleen Robinson

TELEPHONE NO. 915 758-6700

(This space for State Use)

ORIGINAL SIGNED BY

GARY WINK

FIELD REP. II

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

MAR 04 1998

IT 9 N

dp

PAGE 2 - NMGSAU 207

SWABBED WELL. RAN 2-3/8" TBG. & SET O.E. AT 3968'. SPOTTED 7 SKS. TOTAL OYSTER SHELLS & BROKE CIRC. W/PROD. WATER. CIRC. CLEAN. HALLIBURTON SVC. SPOTTED 15 SKS. CLASS H CEMENT FR. 3968' - 3856'. WOC. TAGGED TOP OF CEMENT AT 3940' (PBD). SWABBED WELL. TIH W/5-1/2" X 2-3/8" ARROWSET PKR. ON 2-3/8" IPC TBG. & SET PKR. AT 3799'. CIRC. PKR. FLUID. PRESS. TESTED CSG. TO 540 PSI FOR 30 MIN. HELD OK. CHART ATTACHED. REMOVED BOP & INSTALLED WELLHEAD. RDPU & CLEANED LOCATION. WELL STATUS CHANGED FR. PUMPING OIL WELL TO WATER INJECTION WELL. WELL CLOSED IN PENDING INJECTION LINE INSTALLATION. C-103 TO FOLLOW ON FIRST INJECTION.