Form 3160-5 (August 1999)

) STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

CHNDDV	NOTICES	VND	REPORTS	ON	WEI	10

N.M. JI Cid	FORM APPROVED NS. Division 1004-0135 Expires: November 30, 2000 DC Lab Serial No.
4000 11 10	Expires: November 30, 2000
1625 N. Fre	NC Deal Serial No.
Wahha NIM	-09240-c-03407E

6 If Indian Allottee or Tribe Name

abandoned well. Use Form				o. Il malai, Ala	nee of Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse side					7. If Unit or CA/Agreement, Name and/or No North Monument G/SA Unit	
1. Type of Well				8. Well Name ar	J M.	
Oil Well Gas Well X Other 2. Name of Operator		Water Injec	tion Well.	8. Well Name at	15	
Amerada Hess Corporation				9. API Well No.		
a. Address	3b	Bb. Phone No. (include area code)		30-025-05634		
P.O. Box 840, Seminole, TX 79360		915 758-6778		N .	ol, or Exploratory Area	
Location of Well (Footage, Sec., T., R., M., or Survey I	Description)			Eunice Monu	ment G/SA	
660' FSL, 1980' FEL, Unit O, Sec. 1	8, T19S, R37E.					
				11. County or P	arish, State	
				Lea	N.M.	
12. CHECK APPROPRIATE	BOX(ES) TO INDIC	ATE NATURE OF NO	OTICE, REP	ORT, OR OTH	ER DATA	
TYPE OF SUBMISSION		TYPE	OF ACTION			
Notice of Intent	Acidize	Deepen	Production	(Start/Resume)	Water Shut-Off	
	Alter Casing	Fracture Treat	Reclamatio		Well Integrity	
X Subsequent Report	l == '		吕	<u>-</u>	╡ ゜゜	
	X Casing Repair	New Construction	Recomplet	te	Other	
Final Abandonment Notice	Change Plans	Plug and Abandon	Temporari	ly Abandon		
	Convert to Injection Plug Back Water Die		Water Disp	oosal		
MIRU Aries Well Svc. pulling unit w/6-1/8" bit to 3921' & TOH. TIH 32 min. Held OK. Dumped 3 sks. csg. gun & shot 4 holes at 1850'. Plus cement at 14.1 slurry weight WOC. TIH w/6-1/8" bit, tagged TO csg. to 530 PSI for 32 min. Held 3740'. Attempted to press. test w/pkr. & located csg. leak fr. 21 Plus cement into csg. leak. WOC. Circ. clean & press. tested csg. REP, latched onto & TOH w/REP at at 3773'. Removed BOP & installe	sand on top REP. Est. circ. Hall: followed by 350 s C at 1783', & drick CK. TOH w/REP. csg. w/no results. follow-2190'. Hall: TIH w/6-1/8" bit to 520 PSI for 32 3710'. TIH w/7"	Jarrel Wireline Stiburton Svc. mixesks. Premium Plus d. out cement at 1 TIH w/7" pkr. on TOH w/pkr. TIF burton Svc. mixed to, tagged TOC at 1 min. Held OK. TIX Arrow inj. pkr.	sted csg. to sve. ran Ci and & pumped cement at 1870'. Cin 2-3/8" IPC w/7" REP i & spotted 1977' & dri TIH w/ret on 2-3/8"	to 570 PSI for EL Log. TIH de 200 sks. Pro 14.8 slurry rc. clean & pc tbg. & set set at 3710 de 50 sks. Pro 150 sks. Pro 150 cut cementool, circ. "IPC tbg. &	or w/4" remium weight. press. pkr. at '. TIH emium at at 2240'. sand off set pkr.	
Chart attached. RDPU, cleaned lo		_				
			<u></u>			
14. I hereby certify that the foregoing is true and correct		Title	 AC	CEPTED EC	ND DD	
Name (Printed/Typed) Roy L. Wheeler, Jr.		Bug Su	c. Spec. I	T	R RECORD	
() P. 11 A 1			1		7	
Vay WWW. J.		Date 08/23/200		AUG 3 D	2002	
	S SPACE FOR FERE	MIMINK MYNGRIBHAFIR BALLI	CE USE	CAE		
Approved by	OC F	V. VILLOK IELD REPRESENTATI	VE TOPE PE	GARY GOUR	LEY	
Conditions of approval, if any, are attached. Approval o certify that the applicant holds legal or equitable title to which would entitle the applicant to conduct operations the	of this notice does not warrant those rights in the subject	int or Office	·· W 3147	MARIA WERN	SEPRO 6 2002	

2.33

18:6 W 80MW8

BECENED