

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

| | | | |
|--|---|--|--|
| REPORT ON BEGINNING DRILLING OPERATIONS | | REPORT ON REPAIRING WELL | |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL | | REPORT ON PULLING OR OTHERWISE ALTERING CASING | |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF | X | REPORT ON DEEPENING WELL | |
| REPORT ON RESULT OF PLUGGING OF WELL | | | |

Monument, New Mexico

Place

November 27, 1936

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation State "T" Well No. 6 in the
Company or Operator Lease
NW 1/4 NE 1/4 of Sec. 20, T. 19, R. 37, N. M. P. M.,
Monument Field, Lea County.

The dates of this work were as follows: _____

Notice of intention to do the work was [~~was not~~] submitted on Form C-102 on November 24, 1936 19____
and approval of the proposed plan was [~~was not~~] obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

8-5/8" 32# 8-thd. New Seamless casing was set in this well at 2585' and cemented by the Halliburton Method with 500 sacks.

Casing and fittings were tested with 1200# pump pressure and allowed to stand undisturbed for thirty minutes. No drop in pressure resulted so the cement was then drilled out of the casing and the same test of 1200# pump pressure again applied and allowed to stand undisturbed for thirty minutes. No drop in pressure resulted so the drilling was then resumed.

DUPLICATE

Witnessed by Claud Cook Name Noble Drilling Co. Company Tool-pusher Title

Subscribed and sworn to before me this 30

day of Nov., 1936

Patricia Mahoney
Notary Public

My Commission expires 10-27-39

I hereby swear or affirm that the information given above is true and correct.

Name J. A. Stucky

Position Farm Boss

Representing Amerada Petroleum Corporation
Company or Operator

Address Monument, New Mexico

Remarks:

J. A. Stucky Name
Oil & Gas Inspector Title