Submit 3 Copies To Appropriate District State of New Mexico Office Form C-103 Energy, Minerals and Natural Resources District I Revised March 25, 1999 1625 N. French Dr., Hobbs, NM 87240 WELL API NO. District II OIL CONSERVATION DIVISION 30-025-05706 811 South First, Artesia, NM 87210 5. Indicate Type of Lease District III 2040 South Pacheco 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 STATE X FEE \square District IV 2040 South Pacheco, Santa Fe, NM 87505 6. State Oil & Gas Lease No. B2330 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name: DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: East Eumont Unit Oil Well Gas Well Other Injection 2. Name of Operator 8. Well No. OXY USA WIP Limited Partnership 19246: 3. Address of Operator 9. Pool name or Wildcat P.O. Box 50250 Midland, TX 79710-0250 Eumont Yates 7Rvr On 4. Well Location 1980 feet from the ___ south line and___ 660 feet from the_ line Section Township 19S Range 37E **NMPM** County 10. Elevation (Show whether DR, RKB, RT, GR, etc.) Lea 11. Check Appropriate Box to Indicate, Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON X REMEDIAL WORK ALTERING CASING **TEMPORARILY ABANDON** CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND PULL OR ALTER CASING ABANDONMENT MULTIPLE CASING TEST AND COMPLETION CEMENT JOB OTHER: OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion TD-3912' PBID-3905' PERFS-3823-3837' 8-5/8" 22.7# csg @ 370' W/ 300sx, 12-1/4" hole, TOC-Circ 5-1/2" 15.5# csg @ 3912' W/ 800sx, 7-7/8" hole, TOC-1590'-TS 1. RIH & set CIBP @ 3773', dump 5sx cmt to 3738' 2. M&P 25sx cmt @ 2768-2668' - TAG 3. Perf @ 1507', sqz w/ 35sx cmt to 1407'~ TAG 4. Perf @ 420', sqz w/ 35sx cmt to 320', WOC-TAG THE COMMISSION MUST BE NOTIFIED 24 5. M&P 10sx cmt surface plug HOURS PRIOR TO THE BEGINNING OF 10# MLF between plugs PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE_ _ TITLE Sr. Regulatory Analyst Type or print name David Stewart Telephone No. 915-685-5717 (This space for State use) ORIGINAL SIGNED BY GARY W. WINK

OCIFIFUD REPRESENTATIVE II/STAFF MANAGER

JUL 29 2002

DATE

APPROVED BY_

Conditions of approval, if any:

A CONTRACTOR

OXY USA INC. PROPOSED

EAST EUMONT UNIT 75

SEC 27 T19S R37E LEA NM

0.0 - 370.0' 12-1/4" OD HOLE HHHHHHH 0.0 - 75.0' CEMENT PLUG 10sx 0.0 - 370.0' CEMENT 300sx-CIRC 0.0 - 370.0' 8-5/8" OD SURF CSG 320.0 - 420.0' CEMENT PLUG 35sx 420.0 - 420.0' SQUEEZE PERFS 1407.0 - 1507.0' CEMENT PLUG 35sx 1507.0 - 1507.0' SQUEEZE PERFS 370.0 - 3912.0' 7-7/8' OD HOLE 1590.0 - 3912.0' CEMENT 800sx-TS 0.0 - 3912.0' 5-1/2" OD PROD CSG 2668.0 - 2768.0' CEMENT PLUG 25sx 3738.0 - 3773.0' CEMENT PLUG 5sx 3773.0 - 3773.0' CIBP 3823.0 - 3837.0' ABANDONED PERFS

10: 3912