

**NEW MEXICO OIL CONSERVATION COMMISSION**  
Santa Fe, New Mexico

**MISCELLANEOUS REPORTS ON WELLS**

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<b>X</b>	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

**Monument, New Mexico****April 30, 1936**

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

**Amerada Petroleum Corporation****State "P"**Well No. **2**

in the

Company or Operator

Lease

**NW 1/4 SW 1/4**of Sec. **29**T. **19**R. **37**

N. M. P. M.,

**Monument**

Field,

**1st**

County.

The dates of this work were as follows:

Notice of intention to do the work was (~~received~~) submitted on Form C-102 on **April 27, 1936**

19

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

**DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

**8-5/8" 28# 8-thd. New Electric Weld casing was set in this well at 2495' and cemented by the Halliburton method with 500 sacks of cement.**

**Casing and fittings were tested with 1200# pump pressure and allowed to stand undisturbed for thirty minutes. No drop in pressure resulted. Cement plug was then then drilled out of casing and the same pressure again applied and allowed to stand undisturbed for thirty minutes undisturbed. No drop in pressure resulted. So Drilling was then resumed.**

Witnessed by **Ira French** **Rowan Drilling Co.**

Name

Company

Title

**DUPLICATE**

Subscribed and sworn to before me this **7**

I hereby swear or affirm that the information given above is true and correct.

day of

19 **36**Name **J. H. Stucky**Position **Area Boss**

Representing **Amerada Petroleum Corporation**  
Company or Operator

My Commission expires **10-24-39**Address **Monument, New Mexico**

Remarks:

Name

Title

1CR

*Journal of Management Education* 30(6)