

NEW MEXICO OIL CONSERVATION COMMISSION

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name	
2. Name of Operator Amerada Hess Corporation		8. Farm or Lease Name State "R"	
3. Address of Operator Drawer "D", Monument, New Mexico 88265		9. Well No. #2	
4. Location of Well UNIT LETTER <u>N</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>29</u> TOWNSHIP <u>19-S</u> RANGE <u>37-E</u> NMPM.		10. Field and Pool, or Wildcat Monument - G/SA	
15. Elevation (Show whether DF, RT, GR, etc.) 3609' DF		12. County Lea	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plan to pull rods & pump, check for fill in open hole & pull tbg. Set bridge plug in 6-5/8" csg. at 3750' & cap w/sand. Test 6-5/8" csg. w/1000#. Run bond log & determine top of cement outside 6-5/8" csg. & perf. csg. at top of cement w/2 shots. Run cement retainer & set same. Establish injection rate & attempt to circ. out 8-5/8" csg. Cement thru 6-5/8" csg. perf. w/400 sks. Class "C" neat cement & attempt to circ. out 8-5/8" csg. If cement circulates, close off 8-5/8" & squeeze. WOC & drill out & test. Wash sand fr. top of bridge plug & recover same. Perf. Grayburg San Andres zone in open hole selectively fr. 3810' to 3856', check for fill in open hole. Run pkr. & tbg. & acidize w/5000 gal. 20% NE-FE acid & 4000 gal. gelled water in stages. Swab load, pull tbg. & pkr. re-run tbg., pump & rods & resume prod.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>ELB Fisher</u>	TITLE <u>Supv. Adm. Ser.</u>	DATE <u>3-15-79</u>
APPROVED BY <u>Larry Sexton</u>	TITLE <u>Dist. L. Supv.</u>	DATE <u>MAR 16 1979</u>

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

1940191079

1940191079
1940191079