

| | |
|------------------------|--|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| SANTA FE | |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | |

5a. Indicate Type of Lease
State For

5. State Oil & Gas Lease No.
15533-122

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRAIL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - "A" (FORM C-101) FOR SUCH PROPOSALS.)

1. Name of Operator
Amerada Hess Corporation

2. Address of Operator
Drawer D, Monument, New Mexico 88265

3. Location of Well
UNIT LETTER B 660 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 30 TOWNSHIP 19-S RANGE 37-E NMPM.

4. Indicate Type of Well
OIL WELL GAS WELL OTHER

7. Unit Agreement Name

8. Farm or Lease Name
State "0"

9. Well No.
1

10. Field and Pool, or Wildcat
Eumont Yates 7R Queen

11. Elevation (Show whether DF, RT, GR, etc.)
3646' DF

12. County
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

| | | | |
|--|---|--|---|
| NOTICE OF INTENTION TO: | | SUBSEQUENT REPORT OF: | |
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input type="checkbox"/> | PLUG AND ABANDONMENT <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | | CASING TEST AND CEMENT JOBS <input type="checkbox"/> | |
| OTHER <input type="checkbox"/> | | OTHER <u>Zone abandonment Eumont</u> <input checked="" type="checkbox"/> | |

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103.

Jan. 1980
Pulled rods & plgr. Worked 1½" tbg. free, pulled & laid down same. Pulled & laid down 3½" tbg. Set retrievable bridge plug at 3780' & pkr. at 3728'. Tested bridge plug w/2000# press. Held OK. Spotted 4 sks. sand on top of bridge plug. Set Halliburton cement retainer at 3157', pressured annulus at 500# & squeezed Eumont Yates Seven Rivers Queen zone thru 6-5/8" csg. perf. fr. 3260' to 3560' w/200 sks. Class C cement w/additives. Squeezed 100 sks. into formation, left 56 sks. inside 6-5/8" csg. 2 sks. above retainer and reversed out 42 sks. WOC & drld. hard cement inside 6-5/8" csg. fr. 3148' to 3157' retainer fr. 3157' to 3160' & cement fr. 3160' to 3563' & cement stringers fr. 3563' to 3585'. Circ. hole clean & press. tested squeeze job w/800# & held OK. Eumont zone P & A.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E.B. Fisher TITLE Supv. Adm. Ser. DATE 5-6-80

APPROVED BY _____ TITLE _____ DATE MAY 9 1980

CONDITIONS OF APPROVAL, IF ANY: