

NF MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

**MISCELLANEOUS REPORTS ON WELLS**

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL REPORT ON RESULT OF TEST OF CASING SHUT-OFF REPORT ON RESULT OF PLUGGING OF WELL	REPORT ON REPAIRING WELL REPORT ON PULLING OR OTHERWISE ALTERING CASING REPORT ON DEEPENING WELL
--	--

**Hobbs, New Mexico**

**June 24, 1936**

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the **Continental Oil Co.** State C-30 3

NW/4 Company or Operator **30** Lease **19-S** Well No. **37-E** in the  
**Monument** of Sec. **19-S**, T. **19-S**, R. **37-E**, N. M. P. M.,  
**Lea** Field, **Lea** County.

The dates of this work were as follows: **April 30, May 3, May 16, May 20, 1936**

Notice of intention to do the work was (was not) submitted on Form C-102 on \_\_\_\_\_ 19\_\_\_\_  
 and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

**April 30, well was drilled to 2575' in anhydrite. 8-5/8" OD casing was set at 2574' and cemented with 950 sacks.**

**May 3, casing was tested with 1200# pressure for 30 minutes before and after drilling plug. Casing bailed and tested dry.**

**May 16, well was drilled to total depth of 3885' in Lime. 5 1/2" casing was set at 3854' and cemented with 400 sacks cement.**

**May 20, casing was tested with 1200# pressure for 30 minutes before and after drilling plug. Casing bailed and tested dry.**

Witnessed by **T. S. Offutt** **Amerada** **Lease foreman**  
 Name Company Title

Subscribed and sworn to before me this **24**

day of **June**, 19**36**

*Catrina Johnson*  
 Notary Public

My Commission expires **October 24, 39**

I hereby swear or affirm that the information given above is true and correct.

Name *H. J. Johnston*  
 Position **District Supt.**  
 Representing **Continental Oil Company**  
 Company or Operator  
 Address **Box CC, Hobbs, New Mexico**

Remarks:

Name

Title

