

OIL CONSERVATION DIVISION

P.O. Box 2088 Santa Fe, New Mexico 87504-2088

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO. 30-025-05775
5. Indicate Type of Lease STATE [] FEE [X]
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name NORTH MONUMENT G/SA UNIT BLK. 15
8. Well No. 6
9. Pool name or Wildcat EUNICE MONUMENT G/SA

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE 'APPLICATION FOR PERMIT' (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL [X] GAS WELL [] OTHER []
2. Name of Operator AMERADA HESS CORPORATION
3. Address of Operator DRAWER D, MONUMENT, NM 88265

4. Well Location Unit Letter F : 2310 Feet From The NORTH Line and 2310 Feet From The WEST Line
Section 31 Township 19S Range 37E NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK [] PLUG AND ABANDON [] TEMPORARILY ABANDON [] CHANGE PLANS [] PULL OR ALTER CASING [] OTHER: []
SUBSEQUENT REPORT OF: REMEDIAL WORK [] ALTERING CASING [] COMMENCE DRILLING OPNS. [] PLUG AND ABANDONMENT [] CASING TEST AND CEMENT JOB [] OTHER: TESTED CASING [X]

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 7-6 THRU 7-13-93

MIRU DA&S WELL SER. PULLING UNIT AND TOH WITH RODS & PUMP. REMOVED 9-5/8" HINDERLITER TUBINGHEAD PACKING SLIP ASSEMBLY AND INSTALLED AN ADAPTER FLANGE AND A 6" 900 MANUAL BOP. WITH TBG. TOH. TIH WITH WITH A 6-1/4" DRILL BIT. TAGGED AT 3,861' FOR 69' OF FILL IN OPENHOLE & TOH. TIH WITH A 7" ELDER LOK-SET RETRIEVABLE BRIDGE PLUG SET AT 3,760'. CIRC. CASING WITH 130 BBLs. FRESH WATER & PRESS. TESTED CASING FROM 0' TO 3,760'. PRESS. DECREASED FR. 550 PSI TO 505 PSI IN 30 MINS. RELEASED RBP AND TOH WITH RBP. TIH WITH A 6-1/8" DRILL BIT & 3-3/4" LAFLEUR BAILER. TAGGED TOP OF FILL AT 3,864' AND CLEANED OUT FROM 3,864' TO 3,914'. TOH WITH BAILER ASSEMBLY. TIH WITH 7" BAKER TAC WITH 45,000# SHEAR PINS & 2-7/8" 10V EUE TBG. REMOVED 6" 900 MANUAL BOP & ADAPTER FLANGE AND INSTALLED 9-5/8" HINDERLITER TUBINGHEAD PACKING AND SLIP ASSEMBLY. SET TAC AT 3,767' WITH 14,000# TENSION AND SN AT 3,860'. TIH WITH PUMP & RODS. RIGGED DOWN PULLING UNIT, CLEANED LOCATION AND RESUMED PROD. WELL. TEST OF 7-19-93: PROD. 4 B.O., 5 B.W. & 7 MCFGPD IN 24 HRS.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE [Signature] TITLE SUPVR. ADMIN. SERV. DATE 7-20-93
TYPE OR PRINT NAME ROY L. WHEELER, JR. TELEPHONE NO. 393-2144

(This space for State Use)
Orig. Signed by Paul Kautz Geologist
APPROVED BY [Signature] TITLE [Signature] DATE JUL 27 1993
CONDITIONS OF APPROVAL, IF ANY:

