

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name D. F. Larsen
3. Address of Operator Drawer D, Monument, New Mexico 88265	9. Well No. 1
4. Location of Well UNIT LETTER <u>F</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>32</u> TOWNSHIP <u>19S</u> RANGE <u>37E</u> NMPM.	10. Field and Pool, or WHdcat Eunice Monument G/SA
15. Elevation (Show whether DF, RT, GR, etc.) 3598' DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK PLUG AND ABANDON
TEMPORARILY ABANDON CHANGE PLANS
PULL OR ALTER CASING OTHER

SUBSEQUENT REPORT OF:

REMEDIAL WORK ALTERING CASING
COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT
CASING TEST AND CEMENT JOB OTHER

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

June 27, 1984 to July 2, 1984

Pulled rods, pump & tbg. Ran junk basket in 6-5/8" csg. to 3770'. Set CIBP in 6-5/8" csg. @ 3785'. Spotted perf. acid in 6-5/8" csg. f/3676' to 3770'. & perf. 6-5/8" csg. opposite Grayburg/San Andres zone selectively f/3676' to 3688', 3712' to 3716', 3738' to 3758' and 3762' to 3770' w/total of 120 shots. Ran pkr. and tbg., set pkr. @ 3733' and acidized G/SA zone thru 6-5/8" csg. perf. f/3738' to 3770' w/1000 gal. 15% NE acid using ball sealers as diverter. Swabbed load. Pulled tbg. & pkr. and set retrievable bridge plug in 6-5/8" csg. @ 3733'. Set pkr. @ 3582' and acidized G/SA zone thru 6-5/8" csg. perf. f/3673' to 3728' w/1000 gal 15% NE acid using ball sealers as diverter. Swabbed load. Pulled tbg., pkr., and retrievable bridge plug. Re-ran tbg., pump and rods and resumed production.

No test reported.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dorrell Green

TITLE Production Clerk

DATE 7-6-84

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

JUL - 9 1984

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY: